www.CableCon.co.kr 케이블 콘

IEEE 802.3, ISO/IEC 8802.3 10Base2 and 10Base5

Trunk Cables – Thinnet and Thicknet

Description	Part No.	UL NEC/ C(UL)CEC Type IEC	Standard Lengths ft.	Standard Lengths m	Standard Unit Weight lbs.	Standard Unit Weight kg	Conductor (Stranding) Diameter Nom. DCR	Nominal Core OD (Dielectric) inch	Nominal Core OD (Dielectric) mm	Shielding Material Nom. DCR	Nominal OD inch	Nominal OD mm	Nom. Imp. (Ω)	Nom. Vel. of Prop.	Nominal Capacitance pF/ft.	Nominal Capacitance pF/m	Nominal Attenuation MHz	Nominal Attenuation dB/ 100 ft.	Nominal Attenuation dB/ 100 m
Thinnet 10Base2 • 20 AWG • Stranded (19x32) 0.9 mm Tinned Copper • **Duobond® II** • 93% Tinned Copper Braid																			
Ethernet • Foam HDPE Insulation • Grey PVC Jacket																			
30V 60°C UL AWM Style 1354	**9907**	NEC: CL2, CM CEC: CM	500 U-1000 1000 1640 2500 3280	152 U-305 305 500 762 1000	12.6 25.1 25.1 41.0 62.6 82.2	5.7 11.4 11.4 18.6 28.4 37.3	0.94 mm 20 AWG (19x32) TC 47.9 Ω/km* 28.9 Ω/km**	0.102	2.59	Duobond® II + 93% TC 19.0 Ω/km***	0.185	4.70	50	80%	25.4	83.3	1 10 50 100 200 400 700 900 1000	0.4 1.3 2.9 4.2 6.1 8.9 12.1 13.9 14.8	1.4 4.3 9.5 13.8 20.0 29.2 39.7 45.6 48.6
DEC Part No. 17-01248-00 For Plenum version of 9907, see 89907 or 82907.																			
Plenum • Ethernet • Foam FEP Insulation • Natural Flamarrest® Jacket																			
300V 75°C	**82907**	NEC: CL2P CMP CEC: CMP	† 500 U-1000 † 1000 † 2500	152 U-305 305 762	12.6 23.1 24.0 57.5	5.7 10.5 10.9 26.1	0.94 mm 20 AWG (19x32) TC 47.9 Ω/km* 28.9 Ω/km**	0.095	2.41	Duobond® II + 93% TC 19.0 Ω/km***	0.160	4.06	50	80%	25.4	83.3	1 10 50 100 200 400 700 900 1000	0.4 1.3 2.9 4.2 6.1 9.2 12.9 15.0 16.0	1.4 4.3 9.5 13.8 20.0 30.2 42.3 49.2 52.5
Plenum • Ethernet • Foam FEP Insulation • Grey Fluorocopolymer Jacket																			
300V 150°C	**89907**	NEC: CL2, CM CEC: CM	† 500 † 1000 † 2500	152 305 762	12.6 24.0 60.2	5.7 10.9 27.3	0.94 mm 20 AWG (19x32) TC 47.9 Ω/km* 28.9 Ω/km**	0.095	2.41	Duobond® II + 93% TC 19.0 Ω/km***	0.160	4.06	50	80%	25.4	83.3			see above
DEC Part No. 17-01246-00 Suitable for outdoor and direct burial applications.																			
Thinnet 10Base2 • 12 AWG • Solid 2.05 mm Bare Copper • **Duobond® IV** Quad Shield																			
Ethernet • Foam Polyethylene Insulation • Yellow PVC Jacket																			
30V 60°C UL AWM Style 1478	**9880**	NEC: CL2, CM CEC: CM	500 1000 1640	152 305 500	66.1 131.2 220.2	30.0 59.5 99.9	2.05 mm 12 AWG Solid BC 9.66 Ω/km* 4.66 Ω/km**	0.243	6.17	Duobond® IV Quad Shield 5.0 Ω/km***	0.405	10.29	50	78%	25.9	85.0	1 5 10 50 100 200 400 700 900 1000	0.2 0.4 0.5 1.2 1.7 2.6 3.9 5.5 6.5 6.9	0.6 1.2 1.7 3.9 5.6 8.4 12.8 18.1 21.3 22.6
DEC Part No. 17-00451-00 5.0 Ω/km For Plenum version of 9880, see 89880.																			
Ring-band stripes marked every 2.5 meters to aid users in tap placement.																			
Plenum • Ethernet • Foam FEP Insulation • Orange Fluorocopolymer Jacket																			
150°C	**89880**	NEC: CL2P CMP CEC: CMP	† 1000 † 1640	305 500	134.3 225.1	60.9 102.1	2.05 mm 12 AWG Solid BC 9.66 Ω/km* 4.66 Ω/km**	0.245	6.22	Duobond® IV* Quad Shield 5.0 Ω/km***	0.375	9.53	50	78%	25.9	85.0	1 5 10 50 100 200 400 700 900 1000	0.2 0.4 0.5 1.1 1.6 2.5 3.8 5.6 6.8 7.2	0.6 1.2 1.7 3.8 5.4 8.0 12.5 18.4 22.3 23.6
DEC Part No. 17-00324-00 Suitable for outdoor and direct burial applications.																			
Ring-band stripes marked every 2.5 meters to aid users in tap placement.																			

* DC loop resistance • ** DC resistance inner conductor • *** DC resistance outer conductor • TC = Tinned Copper • BC = Bare Copper • DCR = DC resistance
† Spools and/or UnReel® cartons are one piece, but length may vary ±10% from length shown.

Duobond® II and Duobond® IV see technical information page 23.13.

Not RoHS compliant at time of printing.

www.CableCon.co.kr 케이블 콘

www.CableCon.co.kr 케이블 콘

IEEE 802.4, MAP & Mini-MAP, IEEE 802.7

Broadband Coaxial Cables

Description	Part No.	UL NEC/C(UL)CEC Type IEC	Standard Lengths ft.	Standard Lengths m	Standard Unit Weight lbs.	Standard Unit Weight kg	Conductor (Stranding) Diameter Nom. DCR	Nominal Core OD (Dielectric) inch	Nominal Core OD (Dielectric) mm	Shielding Material Nom. DCR	Nominal OD inch	Nominal OD mm	Nom. Imp. (Ω)	Nom. Vel. of Prop.	Nominal Capacitance pF/ft.	Nominal Capacitance pF/m	Nominal Attenuation MHz	Nominal Attenuation dB/100 ft.	Nominal Attenuation dB/100 m
14 AWG • Solid 1.6 mm Copper-Covered Steel • **Duobond® IV** Quad Shield																			
Gas-Injected Foam Polyethylene Insulation • Grey PVC Jacket																			
	3094A	NEC:	500	152	31.1	14.1	1.63 mm	0.280	7.11	Duobond® IV	0.407	10.34	75	82%	16.2	53.1	1	0.2	0.5
		CL2R	1000	305	62.2	28.2	14 AWG			Quad Shield							2	0.2	0.6
		CMR	† 2000	610	121.9	55.3	Solid CCS			4.9 Ω/km***							5	0.3	0.9
		CEC:					20.0 Ω/km*			7.9 mm							10	0.4	1.2
		CMG					36.1 Ω/km**										20	0.5	1.8
																	50	0.8	2.7
																	100	1.2	3.8
																	200	1.6	5.3
RG-11/U Type			Tap marks every 2.6 meters to aid users in installation. 152 m and 305 m exact 1 pc.							Sweep tested 5 MHz to 400 MHz. CPE jacket optional.							300	2.0	6.6
																	400	2.3	7.6

IEEE 802.5, ISO/IEC 8802.5

IBM Cabling System
Types 1A and 1

Description	Part No.	UL NEC/C(UL)CEC Type IEC	Standard Lengths ft.	Standard Lengths m	Standard Unit Weight lbs.	Standard Unit Weight kg	Conductor (Stranding) Diameter Nom. DCR	Nominal Core OD (Dielectric) inch	Nominal Core OD (Dielectric) mm	Shielding Material Nom. DCR	Nominal OD inch	Nominal OD mm	Nom. Imp. (Ω)	Nom. Vel. of Prop.	Nominal Capacitance pF/ft.	Nominal Capacitance pF/m	Nominal Attenuation MHz	Nominal Attenuation dB/100 ft.	Nominal Attenuation dB/100 m
IBM Type 1a • 22 AWG • Solid 0.6 mm Bare Copper • Each Pair Individually **Beldfoil®** Shielded • 65% Overall Tinned Copper Braid • Rip Cord																			
Flame-Retardant Foam Polyethylene Insulation • Black PVC Jacket																			
	IBM Part No. 9688	NEC:	† 500	152	26.5	12.0	0.64 mm	0.099	2.51	Individual	0.296	7.52	150	–	8.5	27.9	4	0.7	2.2
	4716748	CMG	† 1000	305	50.0	22.7	22 AWG			Beldfoil®	x	x					16	1.3	4.4
	33G2772	CEC:	† 2000	610	102.1	46.3	Solid BC			+ Overall	0.431	10.95					100	3.8	12.3
		CMG	† 3600	1098	190.7	86.5				65% TC Braid							300	6.5	21.4
																	100 ††	4.1	13.4
																	300 ††	7.1	23.3
Rip Cord																	600 ††	10.0	32.9
2-Pair			Meets IEEE 802.5 and TIA/EIA-568-A specifications, ETL verified. For token ring (4/16 Mbps), FDDI over copper, and video applications. IBM qualified type 1A media cable for use in IBM cabling systems. For non-suffix "A" type IBM product, see 1634A below.																
BM Type 1 • 22 AWG • Solid 0.6 mm Bare Copper • Each Pair Individually **Beldfoil®** Shielded • 65% Overall Tinned Copper Braid • Rip Cord																			
Flame-retardant Foam Polyethylene Insulation • Black PVC Jacket																			
	IBM Part No. 1634A	NEC:	† 1000	305	50.0	22.7	0.64 mm	0.099	2.51	Individual	0.296	7.52	150	–	8.5	27.9	4	0.7	2.2
	4716748	CMG	† 2000	610	102.3	46.4	22 AWG			Beldfoil®	x	x					16	1.3	4.4
		CEC:	† 3600	1098	191.1	86.7	Solid BC			+ Overall	0.431	10.95							
		CMG								65% TC Braid									
Rip Cord																			
2-Pair			Meets IEEE 802.5 and TIA/EIA-568-A specifications, ETL verified. IBM qualified type 1A media cable for use in IBM cabling systems. For token ring (4/16 Mbps), FDDI over copper, and video applications.																

* DC loop resistance • ** DC resistance inner conductor • *** DC resistance outer conductor • CCS = Copper-Covered Steel • TC = Tinned Copper • BC = Bare Copper • DCR = DC resistance
† Spools are one piece, but length may vary ±10% from length shown.
†† Common mode

Duobond® IV see technical information page 23.13.

Not RoHS compliant at time of printing

www.CableCon.co.kr 케이블 콘