

Security and Alarm Cables

Commercial Applications Shielded




De- scription	Part No.	UL NEC/ C(UL)CEC Type IEC	Standard Lengths		Standard Unit Weight		Conductor (Stranding) Diameter Nom. DCR	Nominal Insulation OD		Shielding Material Nom. DCR	Nominal OD		Color Code
			ft.	m	lbs.	kg		inch	mm		inch	mm	

24 AWG • Stranded (7x32) 0.6 mm Bare Copper • Beldfoil® Shield • 24 AWG Tinned Copper Drain Wire • Numbered and Color Coded

PVC Insulation • Grey PVC Jacket

300V 75°C	5600FE	NEC: CMR CEC: CMG FT4	U-1000 1000	U-305 305	11.0 9.9	5.0 4.5	0.61 mm 24 AWG (7x32) BC	0.034	0.86	Overall Beldfoil® + Drain Wire (24 AWG TC)	0.120	3.05	see chart 12 (Tech Info Section)
--------------	---------------	--------------------------------	----------------	--------------	-------------	------------	--------------------------------	-------	------	---	-------	------	-------------------------------------



Shorting Fold

2 CDR

De- scription	Part No.	No. of Cond. (CDR)	Standard Lengths		Standard Unit Weight		Conductor (Stranding) Diameter Nom. DCR	Nominal Conductor OD		Shielding Material Nom. DCR	Nominal OD		Application
			ft.	m	lbs.	kg		AWG	Section mm ²		inch	mm	

24 AWG • Stranded (7x0.193) 0.6 mm Bare Copper • Overall Alufoil • Color Coded

PVC Insulation • White Flame-Resistant PVC Jacket (Color Code: see chart 11, Tech Info Section)

500V 70°C										Overall Alufoil			- Alarm systems - Antitrust systems - Smoke survey - Fire survey - Industrial checks
--------------	--	--	--	--	--	--	--	--	--	--------------------	--	--	--



LiY (St) Y

SEC0008	2	328	100	39.7	18.0	(7x0.193) BC	24	0.22			0.150	3.80	
SEC0009	4	328	100	61.7	28.0	(7x0.193) BC	24	0.22			0.165	4.20	
SEC0010	6	328	100	75.0	34.0	(7x0.193) BC	24	0.22			0.181	4.60	
SEC0011	8	328	100	97.0	44.0	(7x0.193) BC	24	0.22			0.209	5.30	
SEC0012	10	328	100	114.6	52.0	(7x0.193) BC	24	0.22			0.228	5.80	
SEC0013	12	328	100	136.7	62.0	(7x0.193) BC	24	0.22			0.240	6.10	
SEC0014	16	328	100	160.9	73.0	(7x0.193) BC	24	0.22			0.276	7.00	
SEC0015	2/2	328	100	83.8	38.0	(7x0.193) BC	24	0.22 + 0.50			0.193	4.90	
SEC0016	4/2	328	100	97.0	44.0	(7x0.193) BC	24	0.22 + 0.50			0.205	5.20	
SEC0017	6/2	328	100	114.6	52.0	(7x0.193) BC	24	0.22 + 0.50			0.232	5.90	
SEC0018	8/2	328	100	141.1	64.0	(7x0.193) BC	24	0.22 + 0.50			0.256	6.50	
SEC0019	10/2	328	100	158.7	72.0	(7x0.193) BC	24	0.22 + 0.50			0.264	6.70	
SEC0020	12/2	328	100	172.0	78.0	(7x0.193) BC	24	0.22 + 0.50			0.272	6.90	
SEC0021	2/2	328	100	97.0	44.0	(7x0.193) BC	24	0.22 + 0.75			0.205	5.20	
SEC0022	4/2	328	100	114.6	52.0	(7x0.193) BC	24	0.22 + 0.75			0.220	5.60	
SEC0023	6/2	328	100	132.3	60.0	(7x0.193) BC	24	0.22 + 0.75			0.244	6.20	
SEC0024	8/2	328	100	143.3	65.0	(7x0.193) BC	24	0.22 + 0.75			0.252	6.40	
SEC0025	10/2	328	100	158.7	72.0	(7x0.193) BC	24	0.22 + 0.75			0.264	6.70	
SEC0026	12/2	328	100	174.2	79.0	(7x0.193) BC	24	0.22 + 0.75			0.283	7.20	

TC = Tinned Copper • BC = Bare Copper • DCR = DC resistance

Security and Alarm Cables

Commercial Applications Shielded



De- scription	Part No.	No. of Pairs	Standard Lengths		Standard Unit Weight		Conductor (Stranding) Diameter Nom. DCR	Nominal Conductor OD		Shielding Material Nom. DCR	Nominal OD		Application
			ft.	m	lbs.	kg		AWG	Section mm ²		inch	mm	

24 AWG • Stranded (7x0.193) 0.6 mm Bare Copper • Mylar® Tape • Overall Alufoil • Color Coded

Thermoplastic M9 Insulation • White FRNC/LSNH Jacket (Color Code: see chart below)

60/90V
70°C

Overall
Alufoil

- Cables for anti-theft installations
- Cables for detection of smokes and fires
- To be used in public areas
(like banks, hospitals, big stores, hotels, theaters)



LiH (St) H

SEC0027	1	328	100	41.9	19.0	(7x0.193) BC	24	0.22		0.157	4.00
SEC0028	2	328	100	66.1	30.0	(7x0.193) BC	24	0.22		0.217	5.50
SEC0029	3	328	100	83.8	38.0	(7x0.193) BC	24	0.22		0.228	5.80
SEC0030	4	328	100	105.8	48.0	(7x0.193) BC	24	0.22		0.260	6.60
SEC0031	5	328	100	132.3	60.0	(7x0.193) BC	24	0.22		0.295	7.50
SEC0032	6	328	100	149.9	68.0	(7x0.193) BC	24	0.22		0.307	7.80
SEC0033	7	328	100	169.8	77.0	(7x0.193) BC	24	0.22		0.319	8.10
SEC0034	8	328	100	194.0	88.0	(7x0.193) BC	24	0.22		0.362	9.20
SEC0035	10	328	100	231.5	105.0	(7x0.193) BC	24	0.22		0.382	9.70
SEC0036	11	328	100	269.0	122.0	(7x0.193) BC	24	0.22		0.406	10.30
SEC0037	1/1	328	100	158.7	72.0	(7x0.193) BC	24	0.22 + 0.50		0.264	6.70
SEC0038	2/1	328	100	172.0	78.0	(7x0.193) BC	24	0.22 + 0.50		0.272	6.90
SEC0039	3/1	328	100	97.0	44.0	(7x0.193) BC	24	0.22 + 0.50		0.205	5.20
SEC0040	4/1	328	100	114.6	52.0	(7x0.193) BC	24	0.22 + 0.50		0.220	5.60
SEC0041	5/1	328	100	132.3	60.0	(7x0.193) BC	24	0.22 + 0.50		0.244	6.20
SEC0042	1/1	328	100	97.0	44.0	(7x0.193) BC	24	0.22 + 0.75		0.260	6.60
SEC0043	2/1	328	100	119.0	54.0	(7x0.193) BC	24	0.22 + 0.75		0.283	7.20
SEC0044	3/1	328	100	145.5	66.0	(7x0.193) BC	24	0.22 + 0.75		0.307	7.80
SEC0045	4/1	328	100	158.7	72.0	(7x0.193) BC	24	0.22 + 0.75		0.323	8.20
SEC0046	5/1	328	100	172.0	78.0	(7x0.193) BC	24	0.22 + 0.75		0.331	8.40

BC = Bare Copper • DCR = DC resistance

Mylar® is a DuPont trademark.

Color Code

Pair No.	Color
1	Red, Black
2	White/Blue, Blue
3	White/Orange, Orange
4	White/Green, Green
5	White/Brown, Brown
6	White/Grey, Grey
7	Red/Blue, Blue
8	Red/Orange, Orange
9	Red/Green, Green
10	Red/Brown, Brown
11	Red/Grey, Grey

Pair No.	Color
12	Black/Blue, Blue
13	Black/Orange, Orange
14	Black/Green, Green
15	Black/Brown, Brown
16	Black/Grey, Grey
17	Violet/Blue, Blue
18	Violet/Orange, Orange
19	Violet/Green, Green
20	Violet/Brown, Brown
21	Violet/Grey, Grey

Security and Alarm Cables
Commercial Applications Shielded




De- scription	Part No.	UL NEC/ C(UL)/CEC Type IEC	Standard Lengths		Standard Unit Weight		Conductor (Stranding) Diameter Nom. DCR	Nominal Insulation OD		Shielding Material Nom. DCR	Nominal OD		Color Code
			ft.	m	lbs.	kg		inch	mm		inch	mm	

22 AWG • Stranded (7x30) 0.8 mm Bare Copper • Beldfoil® Shield • 24 AWG Tinned Copper Drain Wire • Numbered and Color Coded

PVC Insulation • Grey PVC Jacket

300V
75°C
NEC:
CMR
CEC:
CMG FT4
0.76 mm
22 AWG
(7x30) BC
0.040
1.01
Overall
Beldfoil®
+ Drain Wire
(24 AWG TC)
see chart below



Shorting Fold

5500FE	2 CDR	C-500	C-152	5.5	2.5	0.130	3.30
		U-500	U-152	6.6	3.0		
		500	152	6.6	3.0		
		U-1000	U-305	11.9	5.4		
5501FE	3 CDR	C-500	C-152	7.1	3.2	0.138	3.51
		U-500	U-152	7.9	3.6		
		500	152	7.5	3.4		
		U-1000	U-305	15.0	6.8		
5502FE	4 CDR	C-500	C-152	8.6	3.9	0.152	3.86
		U-500	U-152	9.5	4.3		
		500	152	9.5	4.3		
		U-1000	U-305	18.1	8.2		
5503FE	5 CDR	1000	305	22.0	10.0	0.165	4.19
		1000	305	22.0	10.0		
5504FE	6 CDR	C-500	C-152	13.4	6.1	0.179	4.55
		U-500	U-152	15.0	6.8		
		U-1000	U-305	29.1	13.2		
		1000	305	29.1	13.2		
5506FE	8 CDR	U-500	U-152	16.5	7.5	0.196	4.98
		U-1000	U-305	32.0	14.5		
		1000	305	32.0	14.5		
5508FE	10 CDR	U-500	U-152	19.6	8.9	0.230	5.84
		U-1000	U-305	37.9	17.2		
		1000	305	44.1	20.0		

TC = Tinned Copper • BC = Bare Copper • DCR = DC resistance

Color Code

Cond. No.	Color
1	Black
2	Red
3	White
4	Green
5	Brown

Color Code

Cond. No.	Color
6	Blue
7	Orange
8	Yellow
9	Purple
10	Grey

Security and Alarm Cables

Commercial Applications Shielded




De- scription	Part No.	UL NEC / C(UL)/CEC Type IEC	Standard Lengths		Standard Unit Weight		Conductor (Stranding) Diameter Nom. DCR	Nominal Insulation OD		Shielding Material Nom. DCR	Nominal OD		Color Code
			ft.	m	lbs.	kg		inch	mm		inch	mm	

22 AWG • Stranded (7x30) 0.8 mm Bare Copper • Beldfoil® Shield • 24 AWG Tinned Copper Drain Wire • Numbered and Color Coded

Polyethylene Insulation • Grey FRNC/LSNH Jacket

300V 70°C	IEC 60754-2						0.76 mm 22 AWG (7x30) BC	0.049	1.25	Overall Beldfoil® + Drain Wire (24 AWG TC)	see chart below		
--------------	-------------	--	--	--	--	--	--------------------------------	-------	------	---	-----------------	--	--



4500FE	2 CDR	328 1640	100 500	4.0 19.6	1.8 8.9						0.130	3.30	
4501FE	3 CDR	328 1640	100 500	4.6 23.1	2.1 10.5						0.138	3.50	
4502FE	4 CDR	328 1640	100 500	6.0 29.3	2.7 13.3						0.154	3.90	
4504FE	6 CDR	328 1640	100 500	7.7 38.6	3.5 17.5						0.181	4.60	
4506FE	8 CDR	328 1640	100 500	9.7 48.7	4.4 22.1						0.197	5.00	
4508FE	10 CDR	U-500 1000	U-152 305	10.8 53.6	4.9 24.3						0.197	5.00	

TC = Tinned Copper • BC = Bare Copper • DCR = DC resistance

Color Code

Cond. No.	Color
1	Black
2	Red
3	White
4	Green
5	Brown
6	Blue
7	Orange
8	Yellow
9	Purple
10	Grey

Security and Alarm Cables
Commercial Applications Shielded




De- scription	Part No.	UL NEC/ C(UL)CEC Type IEC	Standard Lengths		Standard Unit Weight		Conductor (Stranding) Diameter Nom. DCR	Nominal Insulation OD		Shielding Material Nom. DCR	Nominal OD		Color Code
			ft.	m	lbs.	kg		inch	mm		inch	mm	

20 AWG • Stranded (7x28) 1.0 mm Bare Copper • Beldfoil® Shield • 24 AWG Tinned Copper Drain Wire • Numbered and Color Coded

PVC Insulation • Grey PVC Jacket


300V 75°C	NEC: CMR CEC: CMG FT4						0.96 mm 20 AWG (7x28) BC	0.048	1.21	Overall Beldfoil® + Drain Wire (24 AWG TC)		see chart below	
----------------------	--------------------------------	--	--	--	--	--	--------------------------------	-------	------	---	--	-----------------	--



5400FE	2 CDR	C-500 U-500 500 U-1000 1000	C-152 U-152 152 U-305 305	7.9 9.0 8.6 15.9 15.9	3.6 4.1 3.9 7.2 7.2						0.145	3.68	
5401FE	3 CDR	U-500 500 U-1000 1000	U-152 152 U-305 305	11.0 10.6 20.9 20.9	5.0 4.8 9.5 9.5						0.153	3.89	
5402FE	4 CDR	C-500 U-500 500 U-1000 1000	C-152 U-152 152 U-305 305	11.9 12.6 13.0 24.9 26.0	5.4 5.7 5.9 11.3 11.8						0.168	4.27	
5403FE	5 CDR	U-1000 1000	U-305 305	30.0 30.0	13.6 13.6						0.184	4.67	
5405FE	7 CDR	U-1000 1000	U-305 305	39.0 40.1	17.7 18.2						0.201	5.11	
5407FE	9 CDR	1000	305	51.1	23.2						0.236	5.99	

Polyethylene Insulation • Grey FRNC/LSNH Jacket

300V 70°C	IEC 60754-2						0.96 mm 20 AWG (7x28) BC	0.057	1.45	Overall Beldfoil® + Drain Wire (24 AWG TC)		see chart below	
----------------------	-------------	--	--	--	--	--	--------------------------------	-------	------	---	--	-----------------	--



4400FE	2 CDR	328 1640	100 500	4.6 23.6	2.1 10.7						0.146	3.70	
4401FE	3 CDR	328 1640	100 500	6.0 30.0	2.7 13.6						0.154	3.90	
4402FE	4 CDR	328 1640	100 500	7.5 37.9	3.4 17.2						0.169	4.30	
4403FE	5 CDR	328 1640	100 500	4.6 23.6	2.1 10.7						0.185	4.70	

TC = Tinned Copper • BC = Bare Copper • DCR = DC resistance

Color Code

Cond. No.	Color
1	Black
2	Red
3	White
4	Green
5	Brown

Color Code

Cond. No.	Color
6	Blue
7	Orange
8	Yellow
9	Purple

Security and Alarm Cables

Commercial Applications Shielded




De- scription	Part No.	UL NEC/ C(UL)/CEC Type IEC	Standard Lengths		Standard Unit Weight		Conductor (Stranding) Diameter Nom. DCR	Nominal Insulation OD		Shielding Material Nom. DCR	Nominal OD		Color Code
			ft.	m	lbs.	kg		inch	mm		inch	mm	

18 AWG • Stranded (7x26) 1.2 mm Bare Copper • Beldfoil® Shield • 24 AWG Tinned Copper Drain Wire • Numbered and Color Coded

PVC Insulation • Grey PVC Jacket

300V 75°C	NEC: CMR CEC: CMG FT4	1.22 mm 18 AWG (7x26) BC	0.058	1.47	Overall Beldfoil® + Drain Wire (24 AWG TC)	see chart below
--------------	--------------------------------	--------------------------------	-------	------	---	-----------------



Shorting Fold

5300FE	2 CDR	C-500	C-152	11.0	5.0	0.165	4.19						
		U-500	U-152	12.1	5.5								
		500	152	12.1	5.5								
		U-1000	U-305	22.9	10.4								
		1000	305	22.9	10.4								
5301FE	3 CDR	U-500	U-152	15.4	7.0	0.175	4.45						
		500	152	15.0	6.8								
		U-1000	U-305	30.0	13.6								
		1000	305	30.0	13.6								
5302FE	4 CDR	C-250	C-76	8.8	4.0	0.192	4.88						
		U-500	U-152	19.0	8.6								
		500	152	20.5	9.3								
		U-1000	U-305	35.9	16.3								
		1000	305	37.0	16.8								
5303FE	5 CDR	U-500	U-152	22.5	10.2	0.211	5.36						
		500	152	22.5	10.2								
		U-1000	U-305	43.0	19.5								
		1000	305	45.2	20.5								
5304FE	6 CDR	U-500	U-152	28.4	12.9	0.230	5.84						
		500	152	26.0	11.8								
		1000	305	57.1	25.9								
5305FE	7 CDR	1000	305	57.1	25.9	0.230	5.84						
5306FE	8 CDR	500	152	32.0	14.5	0.270	6.86						
		1000	305	64.2	29.1								
Also available in Natural.													
5307FE	9 CDR	1000	305	71.2	32.3	0.272	6.91						

TC = Tinned Copper • BC = Bare Copper • DCR = DC resistance

Color Code

Cond. No.	Color
1	Black
2	Red
3	White
4	Green
5	Brown
6	Blue
7	Orange
8	Yellow
9	Purple

Security and Alarm Cables

Commercial Applications Shielded



De- scription	Part No.	UL NEC/ C(UL)CEC Type IEC	Standard Lengths		Standard Unit Weight		Conductor (Stranding) Diameter Nom. DCR	Nominal Insulation OD		Shielding Material Nom. DCR	Nominal OD		Color Code
			ft.	m	lbs.	kg		inch	mm		inch	mm	
18 AWG • Stranded (7x26) 1.2 mm Bare Copper • Beldfoil® Shield • 24 AWG Tinned Copper Drain Wire • Numbered and Color Coded													
Polyethylene Insulation • Grey FRNC/LSNH Jacket													
300V 70°C		IEC 60754-2					1.22 mm 18 AWG (7x26) BC	0.068	1.72	Overall Beldfoil® + Drain Wire (24 AWG TC)			see chart below
<p>Shorting Fold</p>													
	4300FE	2 CDR	328 1640	100 500	7.1 35.5	3.2 16.1					0.165	4.20	
	4301FE	3 CDR	328 1640	100 500	9.3 45.9	4.2 20.8					0.177	4.50	
	4302FE	4 CDR	328 1640	100 500	11.7 58.2	5.3 26.4					0.193	4.90	
	4303FE	5 CDR	328 1640	100 500	12.8 63.7	5.8 28.9					0.193	4.90	
	4304FE	6 CDR	328 1640	100 500	16.5 82.7	7.5 37.5					0.228	5.80	
	4306FE	8 CDR	328 1640	100 500	20.5 102.7	9.3 46.6					0.272	6.90	
	4307FE	9 CDR	328 1640	100 500	22.0 110.2	10.0 50.0					0.283	7.20	

TC = Tinned Copper • BC = Bare Copper • DCR = DC resistance

Color Code

Cond. No.	Color
1	Black
2	Red
3	White
4	Green
5	Brown
6	Blue
7	Orange
8	Yellow
9	Purple

Security and Alarm Cables

Commercial Applications Shielded



De- scription	Part No.	No. of Cond. (CDR)	Standard Lengths		Standard Unit Weight		Conductor (Stranding) Diameter Nom. DCR	Nominal Conductor OD		Shielding Material Nom. DCR	Nominal OD		Application
			ft.	m	lbs.	kg		AWG	Section mm ²		inch	mm	

18 AWG • Stranded (32x0.20) 1.2 mm Bare Copper • Overall Alufoil • Color Coded

PVC Insulation • White Flame-Resistant PVC Jacket (Color Code: see chart 11, Tech Info Section)

500V

Overall
Alufoil

- Alarm systems
- Smoke survey
- Fire survey
- Industrial checks



LiY (St) Y

SEC0047	2	328	100	110.2	50.0	(20x0.243) BC	17	1.00	0.220	5.60
SEC0048	3	328	100	132.3	60.0	(20x0.243) BC	17	1.00	0.256	6.50
SEC0049	4	328	100	187.4	85.0	(20x0.243) BC	17	1.00	0.276	7.00
SEC0050	5	328	100	220.5	100.0	(20x0.243) BC	17	1.00	0.319	8.10

BC = Bare Copper • DCR = DC resistance

Security and Alarm Cables
Commercial Applications Shielded




De-scription	Part No.	UL NEC/ C(UL)CEC Type IEC	Standard Lengths		Standard Unit Weight		Conductor (Stranding) Diameter Nom. DCR	Nominal Insulation OD		Shielding Material Nom. DCR	Nominal OD		Color Code
			ft.	m	lbs.	kg		inch	mm		inch	mm	

16 AWG • Stranded (19x29) 1.5 mm Bare Copper • Beldfoil® Shield • 18 AWG Tinned Copper Drain Wire • Numbered and Color Coded

PVC Insulation • Grey PVC Jacket


300V 75°C	NEC: CMR CEC: CMG FT4						1.47 mm 16 AWG (19x29) BC	0.068	1.72	Overall Beldfoil® + Drain Wire (18 AWG TC)			
--------------	--------------------------------	--	--	--	--	--	---------------------------------	-------	------	---	--	--	--



5200FE	2 CDR	U-500	U-152	16.5	7.5						0.188	4.78	Black, Red	
		500	152	16.5	7.5									
		U-1000	U-305	31.1	14.1									
		1000	305	32.0	14.5									
Also available in White.														
5201FE	3 CDR	500	152	21.6	9.8						0.200	5.08	Black, Red, White	
		U-1000	U-305	43.0	19.5									
		1000	305	42.1	19.1									
5202FE	4 CDR	500	152	26.5	12.0						0.220	5.59	Black, Red, White, Green	
		1000	305	54.0	24.5									

Polyethylene Insulation • Grey FRNC/LSNH Jacket

300V 70°C	IEC 60754-2						1.47 mm 16 AWG (19x29) BC	0.077	1.95	Overall Beldfoil® + Drain Wire (18 AWG TC)			
--------------	----------------	--	--	--	--	--	---------------------------------	-------	------	---	--	--	--



4200FE	2 CDR	328	100	9.7	4.4						0.189	4.80	Black, Red
		1640	500	48.1	21.8								
4201FE	3 CDR	328	100	11.9	5.4						0.201	5.10	Black, Red, White
		1640	500	59.5	27.0								
4202FE	4 CDR	328	100	15.2	6.9						0.220	5.60	Black, Red, White, Green
		1640	500	75.8	34.4								

TC = Tinned Copper • BC = Bare Copper • DCR = DC resistance

Security and Alarm Cables

Commercial Applications Shielded




De- scription	Part No.	UL NEC/ C(UL)/CEC Type IEC	Standard Lengths		Standard Unit Weight		Conductor (Stranding) Diameter Nom. DCR	Nominal Insulation OD		Shielding Material Nom. DCR	Nominal OD		Color Code
			ft.	m	lbs.	kg		inch	mm		inch	mm	

14 AWG • Stranded (19x27) 1.9 mm Bare Copper • Beldfoil® Shield • 16 AWG Tinned Copper Drain Wire

PVC Insulation • Grey PVC Jacket


300V 75°C	5100FE	NEC: CL3R	500 1000	152 305	28.4 51.1	12.9 23.2	1.85 mm 14 AWG (19x27) BC	0.087	2.21	Overall Beldfoil® + Drain Wire (16 AWG TC)	0.238	6.05	Black, White
--------------	---------------	--------------	-------------	------------	--------------	--------------	---------------------------------	-------	------	---	-------	------	--------------



5100FE	2 CDR	500 U-1000 1000	152 U-305 305	28.4 48.9 51.1	12.9 22.2 23.2						0.238	6.05	Black, White
5101FE	3 CDR	1000	305	66.1	30.0						0.253	6.43	Black, White, Red

Polyethylene Insulation • Grey FRNC/LSNH Jacket

300V 70°C	4100FE	IEC 60754-2	328 1640	100 500	14.3 71.6	6.5 32.5	1.85 mm 14 AWG (19x27) BC	0.099	2.52	Overall Beldfoil® + Drain Wire (16 AWG TC)	0.240	6.10	Black, White
--------------	---------------	----------------	-------------	------------	--------------	-------------	---------------------------------	-------	------	---	-------	------	--------------




2 CDR

12 AWG • Stranded (19x25) 2.4 mm Bare Copper • Beldfoil® Shield • 16 AWG Tinned Copper Drain Wire

PVC Insulation • Grey PVC Jacket


300V 75°C	5000FE	NEC: CL3R	500 1000	152 305	36.6 67.2	16.6 30.5	2.36 mm 12 AWG (19x25) BC	0.107	2.72	Overall Beldfoil® + Drain Wire (16 AWG TC)	0.272	6.91	Black, White
--------------	---------------	--------------	-------------	------------	--------------	--------------	---------------------------------	-------	------	---	-------	------	--------------



2 CDR

Polyethylene Insulation • Grey FRNC/LSNH Jacket

300V 70°C	4000FE	IEC 60754-2	328 1640	100 500	19.2 95.7	8.7 43.4	2.36 mm 12 AWG (19x25) BC	0.118	3.00	Overall Beldfoil® + Drain Wire (16 AWG TC)	0.272	6.90	Black, White
--------------	---------------	----------------	-------------	------------	--------------	-------------	---------------------------------	-------	------	---	-------	------	--------------



2 CDR

TC = Tinned Copper • BC = Bare Copper • DCR = DC resistance

20 • New Generation® Cables