

Security and Alarm Cables
 Commercial Applications Shielded




De-scription	Part No.	UL NEC/ C(UL)CEC Type IEC	Standard Lengths		Standard Unit Weight		Conductor (Stranding) Diameter Nom. DCR	Nominal Insulation OD		Shielding Material Nom. DCR	Nominal OD		Color Code
			ft.	m	lbs.	kg		inch	mm		inch	mm	

16 AWG • Stranded (19x29) 1.5 mm Bare Copper • Beldfoil® Shield • 18 AWG Tinned Copper Drain Wire • Numbered and Color Coded

PVC Insulation • Grey PVC Jacket

300V 75°C	NEC: CMR CEC: CMG FT4					1.47 mm 16 AWG (19x29) BC	0.068	1.72	Overall Beldfoil® + Drain Wire (18 AWG TC)
--------------	--------------------------------	--	--	--	--	---------------------------------	-------	------	---



Shorting Fold

5200FE	2 CDR	U-500	U-152	16.5	7.5				0.188	4.78	Black, Red
		500	152	16.5	7.5						
		U-1000	U-305	31.1	14.1						
		1000	305	32.0	14.5						

Also available in White.

5201FE	3 CDR	500	152	21.6	9.8				0.200	5.08	Black, Red, White
		U-1000	U-305	43.0	19.5						
		1000	305	42.1	19.1						

5202FE	4 CDR	500	152	26.5	12.0				0.220	5.59	Black, Red, White, Green
		1000	305	54.0	24.5						

Polyethylene Insulation • Grey FRNC/LSNH Jacket

300V 70°C	IEC 60754-2					1.47 mm 16 AWG (19x29) BC	0.077	1.95	Overall Beldfoil® + Drain Wire (18 AWG TC)
--------------	----------------	--	--	--	--	---------------------------------	-------	------	---



Shorting Fold
1.23 mm²

4200FE	2 CDR	328	100	9.7	4.4				0.189	4.80	Black, Red
		1640	500	48.1	21.8						

4201FE	3 CDR	328	100	11.9	5.4				0.201	5.10	Black, Red, White
		1640	500	59.5	27.0						

4202FE	4 CDR	328	100	15.2	6.9				0.220	5.60	Black, Red, White, Green
		1640	500	75.8	34.4						

TC = Tinned Copper • BC = Bare Copper • DCR = DC resistance