

Security Composite Cables

Banana Peel® PTZ Camera Cable Composite Cables Jacketless



De-scription	Part No.	UL NEC/ C(UL)/CEC Type IEC	Standard Lengths		Standard Unit Weight		Shielding Material	Nominal OD		Component	Description	Shielding Material & Nom. DCR	Insulation Material & Colors	Component Jacket Material & Colors	Component OD	
			ft.	m	lbs.	kg		inch	mm						inch	mm

Composite • **(1) Coax** 20 AWG 0.8 mm • **(1) Pair Unshielded** 23 AWG 0.6 mm • **(2) CDR Unshielded** 18 AWG 1.2 mm • **Banana Peel®** Unjacketed, Bonded to Central Spline

PVC Insulation (Pairs) • Foam Insulation (Coax) • Black PVC Jacket																
	300V 75°C	500PTZ	NEC: CMR CEC: CMG FT4 Shaft UL 1666	500 1000	152 305	36.8 71.2	17.5 32.3		0.409 10.40	Video	1-Coax RG59/U 20 AWG 0.81 mm Solid BC	95% BC	Foam Polyethylene 5.76 mm	F-R PV Black	0.227	5.77
										Control	1-Pair 23 AWG 0.57 mm Solid BC	Unshielded	Polyolefin 1.04 mm	PVC Blue	0.118	3.00
											Power	2-Conductor 18 AWG 1.22 mm (7x26) BC	Unshielded	PVC 2.20 mm	PVC White	0.171

Kötter approved

Composite • **(1) Coax** 20 AWG 0.8 mm • **(1) Pair Shielded** 22 AWG 0.6 mm • 22 AWG Drain Wire • **(2) CDR Unshielded** 18 AWG 1.2 mm • **Banana Peel®** Unjacketed, Bonded to Central Spline

PVC Insulation (Pairs) • Foam Insulation (Coax) • Black PVC Jacket																
	300V 75°C	501PTZ	NEC: CMR CEC: CMG FT4 Shaft UL 1666	500 1000	152 305	41.0 76.1	18.6 34.5		0.417 10.60	Video	1-Coax RG59/U 20 AWG 0.81 mm Solid BC	95% BC	Foam Polyethylene 5.76 mm	F-R PV Black	0.219	5.57
										Control	1-Pair 22 AWG 0.76 mm (7x30) BC	Overall Beldfoil® + Drain Wire (22 AWG TC)	Polyolefin 1.57 mm	PVC Blue	0.177	4.50
											Power	2-Conductor 18 AWG 1.22 mm (7x26) BC	Unshielded	PVC 2.20 mm	PVC White	0.171

Kötter approved

Composite • **(1) Coax** 20 AWG 0.8 mm • **(1) Pair Shielded** 18 AWG 1.2 mm • 20 AWG Drain Wire • **(2) CDR Unshielded** 18 AWG 1.2 mm • **Banana Peel®** Unjacketed, Bonded to Central Spline

PVC Insulation (Pairs) • Foam Insulation (Coax) • Black PVC Jacket																
	300V 75°C	502PTZ	NEC: CMR CEC: CMG FT4 Shaft UL 1666	500 1000	152 305	50.0 93.9	22.7 42.6		0.453 11.50	Video	1-Coax RG59/U 20 AWG 0.81 mm Solid BC	95% BC	Foam Polyethylene 5.76 mm	F-R PV Black	0.219	5.57
										Control	1-Pair 18 AWG 1.24 mm (19x30) BC	Overall Beldfoil® + Drain Wire (20 AWG TC)	Polyolefin 2.03 mm	PVC Blue	0.219	5.56
											Power	2-Conductor 18 AWG 1.22 mm (7x26) BC	Unshielded	PVC 2.20 mm	PVC White	0.171

Kötter approved

TC = Tinned Copper • BC = Bare Copper • DCR = DC resistance