

Introduction

To assist you in selecting the proper cable for your application, both the suggested working voltages and the maximum temperature ratings are indicated for each applicable product in this section.

Extended Temperature and Chemical Resistant Cable Range Nominal Temperature Operating Ranges (°C)

-100°	-80°	-60°	-40°	-20°	0	20°	40°	60°	80°	100°	120°	140°	160°	180°	200°	220°	240°	
			-40°	TPE										150°C				
			-50°	Silicone										180°C				
			-100°	FEP										205°C				
			-50°	Glass Fiber										350°C				
			-50°	S-Glass Fiber										400°C				
			-50°	Mica										1250°C				
			-50°	Micaflame										1550°C				

Index by Voltage and Temperature Rating

Multicore Section	Page No.	
300V, 150°C	TPE 2-7 Conductors	4.15
	TPE 2-7 Conductors Overall Braid	4.16
300V, 180°C	Silicone Rubber FRNC 2-5 Conductors	4.17
	Silicone Rubber FRNC 6-25 Conductors	4.18 – 4.19
	Silicone Rubber FRNC 2-5 Conductors (H05SS-F)	4.20
	Silicone Rubber FRNC 2-24 Conductors	4.21 – 4.23
	Steel Wire Braid (SWB)	
	Silicone Rubber FRNC 2-7 Conductors Overall Braid	4.24
	Silicone Rubber FRNC 2-30 Conductors Heavy Duty	4.25 – 4.26
Silicone Rubber FRNC 2-30 Conductors Heavy Duty Overall Braid		
300V, 205°C	FEP 2-7 Conductors	4.29
300V, 350°C	Glass Fiber Serving 2-4 Conductors Glass Braid	4.31
	Glass Fiber Serving 2-4 Conductors Glass Braid Steel Wire Braid (SWB)	4.32
300V, 1150°C	Micaflame® 2-5 Conductors Glass Braid	4.34
380V, 1250°C	Mica 2-5 Conductors Ceramic Braid	4.33
	Steel Wire Braid (SWB)	
450V, 75°C	PVC 07BQ-F 2-4 Conductors	4.38
500V, 80°C	PVC LiY(St)CY 2-12 Conductors	4.35 – 4.36
600V, 205°C	FEP 2-7 Conductors Overall Braid	4.30
750V, 80°C	PVC LiY CY 1-10 Conductors	4.37 – 4.38