



UL Control Cable

600V Type MC Metal Clad Cables


Industrial Grade Sunlight- and Oil-Resistant Jackets

Description	Part Number		No. of Cond.	Insulation Thickness		Outer Jacket Thickness		Armor OD		Nominal OD		Minimum Bend Radius	
	Aluminum Armor	Steel Armor		Inch	mm	Inch	mm	Inch	mm	Inch	mm	Inch	mm
10 AWG Stranded (7x18) Bare Copper Conductors • 10 AWG Bare Copper Ground Wire													
Aluminum or Steel Interlocked Armor • Cross-linked Polyethylene Insulation • PVC Jacket													
NEC: MC	27257	28257	2	.030	.76	.050	1.27	.56	14.22	.67	17.02	8.4	213.36
	27258	28258	3	.030	.76	.050	1.27	.58	14.73	.69	17.53	8.6	218.44
	27259	28259	4	.030	.76	.050	1.27	.62	15.75	.74	18.80	9.2	233.68
	27281	28281	5	.030	.76	.050	1.27	.68	17.27	.79	20.07	12.8	325.12
	27282	28282	6	.030	.76	.050	1.27	.74	18.80	.84	21.34	10.4	264.16
	27283	28283	7	.030	.76	.050	1.27	.74	18.80	.84	21.34	10.4	264.16
	27284	28284	8	.030	.76	.050	1.27	.81	20.57	.92	23.37	11.2	284.48
	27541	28541	9	.030	.76	.050	1.27	.87	22.10	.98	24.89	11.8	299.72
	27285	28285	10	.030	.76	.050	1.27	.89	22.61	1.03	26.16	13.3	337.82
	27286	28286	12	.030	.76	.050	1.27	1.01	25.65	1.12	28.45	13.7	347.98
	27287	28287	15	.030	.76	.050	1.27	1.09	27.69	1.22	30.99	14.8	375.92
	27288	28288	20	.030	.76	.055	1.40	1.22	30.99	1.35	34.29	16.2	411.48
	27289	28289	25	.030	.76	.055	1.40	1.32	33.53	1.47	37.34	17.8	452.12
	27290	28290	30	.030	.76	.055	1.40	1.42	36.07	1.55	39.37	18.6	472.44

8 AWG Stranded (7x16) Bare Copper Conductors • 10 AWG Bare Copper Ground Wire

Aluminum or Steel Interlocked Armor • Cross-linked Polyethylene Insulation • PVC Jacket													
NEC: MC	27291	28291	2	.045	1.14	.050	1.27	.70	17.78	.81	20.57	9.8	248.92
	27260	28260	3	.045	1.14	.050	1.27	.72	18.29	.82	20.83	10.2	259.08
	27261	28261	4	.045	1.14	.050	1.27	.78	19.81	.88	22.35	10.9	276.86

6 AWG Stranded (7x14) Bare Copper Conductors • 8 AWG Bare Copper Ground Wire

Aluminum or Steel Interlocked Armor • Cross-linked Polyethylene Insulation • PVC Jacket													
NEC: MC	27293	28293	2	.045	1.14	.050	1.27	.76	19.30	.87	22.10	10.7	271.78
	27262	28262	3	.045	1.14	.050	1.27	.80	20.32	.90	22.86	11.2	284.48
	27263	28263	4	.045	1.14	.050	1.27	.87	22.10	.97	24.64	12.1	307.34

Color Code: For sizes 14, 12, 10, use ICEA Table E2 with printed numbers.

For sizes 8 and larger, use ICEA Method 4 with printed numbers.

Non-stocked items. Check length available for specific construction. Minimum order may apply.