

UL Control Cable


600V Type MC Metal Clad Cables

Industrial Grade Sunlight- and Oil-Resistant Jackets


Description	Part Number		No. of Cond.	Insulation Thickness		Outer Jacket Thickness		Armor OD		Nominal OD		Minimum Bend Radius	
	Aluminum Armor	Steel Armor		Inch	mm	Inch	mm	Inch	mm	Inch	mm	Inch	mm

4 AWG Stranded (7x12) Bare Copper Conductors • 8 AWG Bare Copper Ground Wire**Aluminum or Steel Interlocked Armor • Cross-linked Polyethylene Insulation • PVC Jacket**


NEC: MC	27264	28264	3	.045	1.14	.050	1.27	.90	22.86	1.00	25.40	13.1	332.74
	27265	28265	4	.045	1.14	.050	1.27	1.97	50.04	1.08	27.43	14.2	360.68

**2 AWG** Stranded (7x10) Bare Copper Conductors • 6 AWG Bare Copper Ground Wire**Aluminum or Steel Interlocked Armor • Cross-linked Polyethylene Insulation • PVC Jacket**


NEC: MC	27267	28267	3	.045	1.14	.050	1.27	1.02	25.91	1.13	28.70	14.7	373.38
	27268	28268	4	.045	1.14	.050	1.27	1.11	28.19	1.22	30.99	16.0	406.40

**Composite 14 AWG (7x22) and 12 AWG (7x20) Stranded Bare Copper Conductors • 12 AWG Bare Copper Ground Wire****Aluminum or Steel Interlocked Armor • Cross-linked Polyethylene Insulation • PVC Jacket**


NEC: MC	27428	28428	3c/14	.030	.76	.050	1.27	.70	17.78	.81	20.57	9.7	246.38
			3c/12	.030	.76								

**Composite 14 AWG (7x22) and 10 AWG (7x18) Stranded Bare Copper Conductors • 10 AWG Bare Copper Ground Wire****Aluminum or Steel Interlocked Armor • Cross-linked Polyethylene Insulation • PVC Jacket**


NEC: MC	27429	28429	3c/14	.030	.76	.050	1.27	.74	18.80	.85	21.59	10.2	259.08
			3c/10	.030	.76								

**Composite 14 AWG (7x22) and 8 AWG (7x16) Stranded Bare Copper Conductors • 10 AWG Bare Copper Ground Wire****Aluminum or Steel Interlocked Armor • Cross-linked Polyethylene Insulation • PVC Jacket**

NEC: MC	27430	28430	3c/14	.030	.76	.050	1.27	.83	21.08	.94	23.88	11.2	284.48
			3c/8	.045	1.14								

**Composite 14 AWG (7x22) and 6 AWG (7x14) Stranded Bare Copper Conductors • 8 AWG Bare Copper Ground Wire****Aluminum or Steel Interlocked Armor • Cross-linked Polyethylene Insulation • PVC Jacket**

NEC: MC	27431	28431	3c/14	.030	.76	.050	1.27	.89	22.61	1.01	25.65	12.0	304.80
			3c/6	.045	1.14								



Color Code: For sizes 14, 12, 10, use ICEA Table E2 with printed numbers.

For sizes 8 and larger, use ICEA Method 4 with printed numbers.

Non-stocked items. Check length available for specific construction. Minimum order may apply.