

CSA Control Cable


600V CIC Multi-conductor Cables

Description	Part Number	No. of Cond.	Cable Weight		Insulation Thickness		Jacket Thickness		Nominal OD	
			Lbs. / 1000 Ft.	kg/km	Inch	mm	Inch	mm	Inch	mm

14 AWG Stranded (7x22) Bare Copper Conductors

Cross-linked Polyethylene Insulation • Black PVC Jacket (Color Code: Black and Numbered)

CSA C22.2#131, Type CIC	22100	2	62	92	.030	.76	.045	1.14	.367	9.32
CSA C22.2#0.3, Clause 4.31 Low Acid Gas FT4 Flame Test	22101	3	81	121	.030	.76	.045	1.14	.388	9.86
	22102	4	101	150	.030	.76	.045	1.14	.423	10.74
	22103	5	122	182	.030	.76	.045	1.14	.462	11.74
	22104	6	143	213	.030	.76	.045	1.14	.504	12.80
	22105	7	160	238	.030	.76	.045	1.14	.504	12.80
	22106	8	197	293	.030	.76	.060	1.52	.576	14.63
	22107	9	220	327	.030	.76	.060	1.52	.618	15.70
	22108	10	226	336	.030	.76	.060	1.52	.669	17.00
	22110	12	279	415	.030	.76	.060	1.52	.689	17.50
	22114	16	357	531	.030	.76	.060	1.52	.764	19.41
	22118	20	467	695	.030	.76	.080	2.03	.886	22.50




Rip Cord

-25°C Installed
-40°C to +90°C (Dry) (75°C Wet)

12 AWG Stranded (7x20) Bare Copper Conductors

Cross-linked Polyethylene Insulation • Black PVC Jacket (Color Code: Black and Numbered)

CSA C22.2#131, Type CIC	22120	2	82	122	.030	.76	.045	1.14	.405	10.29
CSA C22.2#0.3, Clause 4.31 Low Acid Gas FT4 Flame Test	22121	3	109	162	.030	.76	.045	1.14	.429	10.90
	22122	4	140	208	.030	.76	.045	1.14	.469	11.91
	22123	5	170	253	.030	.76	.045	1.14	.515	13.08
	22124	6	214	319	.030	.76	.060	1.52	.591	15.01
	22125	7	240	357	.030	.76	.060	1.52	.591	15.01
	22126	8	270	402	.030	.76	.060	1.52	.639	16.23
	22127	9	302	449	.030	.76	.060	1.52	.687	17.45
	22128	10	336	500	.030	.76	.060	1.52	.745	18.92
	22130	12	390	580	.030	.76	.060	1.52	.768	19.51
	22134	16	584	869	.030	.76	.080	2.03	.893	22.68
	22138	20	655	975	.030	.76	.080	2.03	.992	25.20




Rip Cord

-25°C Installed
-40°C to +90°C (Dry) (75°C Wet)

10 AWG Stranded (7x18) Bare Copper Conductors

Cross-linked Polyethylene Insulation • Black PVC Jacket (Color Code: Black and Numbered)

CSA C22.2#131, Type CIC	22140	2	148	220	.030	.76	.045	1.14	.736	18.69
CSA C22.2#0.3, Clause 4.31 Low Acid Gas FT4 Flame Test	22141	3	189	281	.030	.76	.045	1.14	.763	19.38
	22142	4	248	369	.030	.76	.060	1.52	.839	21.31
	22143	5	293	436	.030	.76	.060	1.52	.891	22.63
	22144	6	338	503	.030	.76	.060	1.52	.944	23.98
	22145	7	378	563	.030	.76	.060	1.52	.944	23.98
	22146	8	424	631	.030	.76	.060	1.52	.999	25.38
	22147	9	469	698	.030	.76	.060	1.52	1.074	27.28
	22148	10	548	816	.030	.76	.080	2.03	1.182	30.02
	22150	12	631	939	.030	.76	.080	2.03	1.209	30.71
	22152	14	717	1067	.030	.76	.080	2.03	1.255	31.88
	22154	16	805	1198	.030	.76	.080	2.03	1.307	33.20



Rip Cord

-25°C Installed
-40°C to +90°C (Dry) (75°C Wet)


CSA Control Cable

600V CIC Multi-conductor Cables

Description	Part Number	No. of Cond.	Cable Weight		Insulation Thickness		Jacket Thickness		Nominal OD	
			Lbs./1000 Ft.	kg/km	Inch	mm	Inch	mm	Inch	mm

8 AWG Stranded (7x16) Bare Copper Conductors**Cross-linked Polyethylene Insulation • Black PVC Jacket** (Color Code: Black and Numbered)

CSA C22.2#131, Type CIC	22160	2	240	357	.045	1.14	.060	1.52	.863	21.92
CSA C22.2#0.3, Clause 4.31 Low Acid Gas FT4 Flame Test	22161	3	308	458	.045	1.14	.060	1.52	.898	22.81
	22162	4	379	564	.045	1.14	.060	1.52	.957	24.31




Rip Cord

-25°C Installed
-40°C to +90°C (Dry) (75°C Wet)

6 AWG Stranded (7x14) Bare Copper Conductors**Cross-linked Polyethylene Insulation • Black PVC Jacket** (Color Code: Black and Numbered)

CSA C22.2#131, Type CIC	22170	2	279	415	.060	1.52	.060	1.52	.711	18.06
CSA C22.2#0.3, Clause 4.31 Low Acid Gas FT4 Flame Test	22171	3	383	570	.060	1.52	.060	1.52	.756	19.20




Rip Cord

-25°C Installed
-40°C to +90°C (Dry) (75°C Wet)

4 AWG Stranded (7x12) Bare Copper Conductors**Cross-linked Polyethylene Insulation • Black PVC Jacket** (Color Code: Black and Numbered)

CSA C22.2#131, Type CIC	22180	2	390	580	.060	1.52	.060	1.52	.800	20.32
CSA C22.2#0.3, Clause 4.31 Low Acid Gas FT4 Flame Test	22181	3	580	863	.060	1.52	.080	2.03	.891	22.63



Rip Cord

-25°C Installed
-40°C to +90°C (Dry) (75°C Wet)