



**CSA Control Cable**

## 600V Teck90 Cables

Description	Part No.	No. of Cond.	Cable Weight		Inner Jacket OD		Armor OD		Outer Jacket		Maximum Pull Tension		Minimum Bend Radius	
			Lbs./1000 Ft.	kg/km	Inch	mm	Inch	mm	Inch	mm	Lbs.	N	Inch	mm
<b>14 AWG Stranded (7x22) Bare Copper Conductors • 14 AWG Bare Copper Ground Wire</b>														
<b>Aluminum Interlocked Armor • .030" (.76mm) XLPE Insulation • PVC Inner Jacket • Black PVC Outer Jacket</b>														
CSA C22.2#131 FT4 Flame Test  Rip Cord	<b>C5500</b>	2	198	296	.36	9.14	.56	14.22	.66	16.76	108	481	7.8	198.12
	<b>C5501</b>	3	222	331	.39	9.91	.58	14.73	.66	16.76	162	721	8.2	208.28
	<b>C5502</b>	4	251	375	.42	10.67	.62	15.75	.71	18.03	216	961	8.5	215.90
	<b>C5503</b>	5	284	424	.47	11.94	.66	16.76	.74	18.80	270	1202	9.0	228.60
	<b>C5504</b>	6	317	473	.51	12.95	.70	17.78	.78	19.81	324	1442	9.5	241.30
	<b>C5505</b>	7	331	494	.51	12.95	.70	17.78	.78	19.81	378	1682	9.5	241.30
	<b>C5506</b>	8	414	618	.58	14.73	.77	19.56	.86	21.84	432	1922	10.4	264.16
	<b>C5508</b>	10	510	761	.67	17.02	.93	23.62	.95	24.13	540	2403	12.3	312.42
	<b>C5510</b>	12	551	822	.69	17.53	.95	24.13	.97	24.64	648	2884	12.6	320.04
	<b>C5513</b>	15	636	949	.77	19.56	1.03	26.16	1.11	28.19	810	3605	14.1	358.14
	<b>C5518</b>	20	810	1209	.90	22.86	1.16	29.46	1.24	31.50	1080	4806	15.1	383.54
	<b>C5523</b>	25	948	1415	.90	22.86	1.24	31.50	1.33	33.78	1350	6008	16.1	408.94
	<b>C5528</b>	30	1047	1563	1.05	26.67	1.30	33.02	1.40	35.56	1620	7209	16.8	426.72
	<b>C5529</b>	40	1310	1955	1.20	30.48	1.42	36.07	1.51	38.35	2160	9612	18.3	464.82
HAZ LOC CSA C22.2#0.3 Clause 4.31 Low Acid Gas	<b>C6064</b>	50	1620	2418	1.35	34.29	1.60	40.64	1.66	42.16	2700	12015	20.5	520.70

**12 AWG Stranded (7x20) Bare Copper Conductors • 14 AWG Bare Copper Ground Wire**

Description	Part No.	No. of Cond.	Cable Weight		Inner Jacket OD		Armor OD		Outer Jacket		Maximum Pull Tension		Minimum Bend Radius	
			Lbs./1000 Ft.	kg/km	Inch	mm	Inch	mm	Inch	mm	Lbs.	N	Inch	mm
<b>12 AWG Stranded (7x20) Bare Copper Conductors • 14 AWG Bare Copper Ground Wire</b>														
<b>Aluminum Interlocked Armor • .030" (.76mm) XLPE Insulation • PVC Inner Jacket • Black PVC Outer Jacket</b>														
CSA C22.2#131 FT4 Flame Test  Rip Cord	<b>C5530</b>	2	225	336	.41	10.41	.60	15.24	.69	17.53	172	765	8.3	210.82
	<b>C5531</b>	3	261	390	.43	10.92	.62	15.75	.70	17.78	258	1148	8.6	218.44
	<b>C5532</b>	4	301	449	.47	11.94	.66	16.76	.73	18.54	344	1531	9.1	231.14
	<b>C5533</b>	5	348	519	.52	13.21	.71	18.03	.78	19.81	430	1914	9.1	231.14
	<b>C5534</b>	6	435	649	.59	14.99	.78	19.81	.86	21.84	516	2296	10.5	266.70
	<b>C5535</b>	7	450	672	.59	14.99	.78	19.81	.86	21.84	602	2679	10.5	266.70
	<b>C5536</b>	8	506	755	.64	16.26	.83	21.08	.92	23.37	688	3062	11.1	281.94
	<b>C5538</b>	10	633	945	.75	19.05	1.01	25.65	1.02	25.91	860	3827	13.3	337.82
	<b>C5540</b>	12	696	1039	.77	19.56	1.03	26.16	1.12	28.45	1032	4592	13.5	342.90
	<b>C5543</b>	15	823	1228	.90	22.86	1.16	29.46	1.24	31.50	1290	5741	15.1	383.54
	<b>C5548</b>	20	1035	1545	.99	25.15	1.25	31.75	1.34	34.04	1720	7654	16.5	419.10
	<b>C5553</b>	25	1230	1836	1.10	27.94	1.36	34.54	1.45	36.83	2150	9568	17.6	447.04
	<b>C5558</b>	30	1390	2075	1.20	30.48	1.46	37.08	1.51	38.35	2580	11481	17.6	447.04

HAZ LOC  
 CSA C22.2#0.3 Clause 4.31 Low Acid Gas

XLPE = Cross-linked Polyethylene

Color Code: 2 conductors — Black, White (If required, a Red conductor can be used in place of White.)  
 3 conductors — Black, Red, Blue (If required, a White conductor can be used in place of Blue.)  
 4 conductors — Black, Red, Blue, White  
 5 or more conductors — Black and numbered