



CSA Control Cable

600V Teck90 Cables

Description	Part No.	No. of Cond.	Cable Weight		Inner Jacket OD		Armor OD		Outer Jacket		Maximum Pull Tension		Minimum Bend Radius	
			Lbs./1000 Ft.	kg/km	Inch	mm	Inch	mm	Inch	mm	Lbs.	N	Inch	mm
10 AWG Stranded (7x18) Bare Copper Conductors • 12 AWG Bare Copper Ground Wire														
Aluminum Interlocked Armor • .030" (.76mm) XLPE Insulation • PVC Inner Jacket • Black PVC Outer Jacket														
CSA C22.2#131 FT4 Flame Test  Rip Cord	C5560	2	278	415	.48	12.19	.66	16.76	.72	18.29	296	1317	8.9	226.06
	C5561	3	327	488	.50	12.70	.70	17.78	.75	19.05	444	1976	9.2	233.68
	C5562	4	405	604	.57	14.48	.77	19.56	.79	20.07	592	2634	10.1	256.64
	C5563	5	487	727	.63	16.00	.83	21.08	.93	23.62	740	3293	11.5	292.10
	C5564	6	556	830	.68	17.27	.88	22.35	.93	23.62	888	3952	11.5	292.10
	C5565	7	627	936	.69	17.53	.89	22.61	.99	25.15	1036	4610	11.8	299.72
	C5566	8	739	1103	.74	18.80	.94	23.88	1.00	25.40	1184	5269	12.4	314.96
	C5568	10	964	1439	.84	21.34	1.10	27.94	1.24	31.50	1480	6586	14.4	365.76
	C5570	12	1067	1593	.93	23.62	1.19	30.23	1.26	32.00	1776	7903	15.6	396.24
	C5573	15	1297	1936	.99	25.15	1.25	31.75	1.37	34.80	2220	9879	16.3	414.02
HAZ LOC CSA C22.2#0.3 Clause 4.31 Low Acid Gas	C5578	20	1546	2307	1.13	28.70	1.39	35.31	1.47	37.34	2960	13172	16.9	429.26
	C5579	25	1802	2690	1.26	32.00	1.52	38.61	1.60	40.64	3700	16465	19.7	500.38
	C5580	30	2142	3197	1.34	34.04	1.60	40.64	1.66	42.16	4440	19758	20.6	523.24

8 AWG Stranded (7x16) Bare Copper Conductors • 10 AWG Bare Copper Ground Wire

Description	Part No.	No. of Cond.	Cable Weight		Inner Jacket OD		Armor OD		Outer Jacket		Maximum Pull Tension		Minimum Bend Radius	
			Lbs./1000 Ft.	kg/km	Inch	mm	Inch	mm	Inch	mm	Lbs.	N	Inch	mm
Aluminum Interlocked Armor • .045" (1.14mm) XLPE Insulation • PVC Inner Jacket • Black PVC Outer Jacket														
CSA C22.2#131 FT4 Flame Test  Rip Cord	C5583	2	407	607	.59	14.99	.78	19.81	.86	21.84	384	1709	10.6	269.24
	C5581	3	471	703	.63	16.00	.83	21.08	.90	22.86	576	2563	10.8	274.32
	C5582	4	606	904	.69	17.53	.89	22.61	.97	24.64	768	3418	12.5	317.50
Dual Rated 600V, 1000V HAZ LOC CSA C22.2#0.3 Clause 4.31 Low Acid Gas														

XLPE = Cross-linked Polyethylene

Color Code: 2 conductors — Black, White (if required, a Red conductor can be used in place of White.)
 3 conductors — Black, Red, Blue (if required, a White conductor can be used in place of Blue.)
 4 conductors — Black, Red, Blue, White
 5 or more conductors — Black and numbered