


CSA Control Cable

1000V Teck90 Cables

Description	Part No.	No. of Cond.	Cable Weight		Inner Jacket OD		Armor OD		Outer Jacket		Maximum Pull Tension		Minimum Bend Radius	
			Lbs./1000 Ft.	kg/km	Inch	mm	Inch	mm	Inch	mm	Lbs.	N	Inch	mm

6 AWG Stranded (7x14) Bare Copper Conductors • 8 AWG Bare Copper Ground Wire**Aluminum Interlocked Armor • .060" (1.53mm) XLPE Insulation • PVC Inner Jacket • Black PVC Outer Jacket**


CSA C22.2#131 FT4 Flame Test	C5590	2	567	844	.73	18.54	.99	25.15	1.10	27.94	610	2713	12.8	325.12
	C5591	3	685	1019	.78	19.81	1.04	26.42	1.15	29.21	915	4072	13.4	340.36
	C5592	4	927	1380	.89	22.61	1.15	29.21	1.24	31.50	1220	5429	14.9	378.46



Rip Cord

HAZ LOC
CSA C22.2#0.3 Clause 4.31 Low Acid Gas**4 AWG Stranded (7x12) Bare Copper Conductors • 8 AWG Bare Copper Ground Wire****Aluminum Interlocked Armor • .060" (1.53mm) XLPE Insulation • PVC Inner Jacket • Black PVC Outer Jacket**


CSA C22.2#131 FT4 Flame Test	C5601	3	961	1430	.91	23.11	1.17	29.72	1.23	31.24	1455	6475	15.2	386.08
	C5602	4	1202	1794	.91	23.11	1.25	31.75	1.33	33.78	1940	8633	16.2	411.48



Rip Cord

HAZ LOC
CSA C22.2#0.3 Clause 4.31 Low Acid Gas**3 AWG Stranded (7x11) Bare Copper Conductors • 6 AWG Bare Copper Ground Wire****Aluminum Interlocked Armor • .060" (1.53mm) XLPE Insulation • PVC Inner Jacket • Black PVC Outer Jacket**


CSA C22.2#131 FT4 Flame Test	C5611	3	1126	1681	.97	24.64	1.23	31.24	1.30	33.02	1836	8170	15.8	401.32
---------------------------------	--------------	---	------	------	-----	-------	------	-------	------	-------	------	------	------	--------



Rip Cord

HAZ LOC
CSA C22.2#0.3 Clause 4.31 Low Acid Gas**2 AWG Stranded (7x10) Bare Copper Conductors • 6 AWG Bare Copper Ground Wire****Aluminum Interlocked Armor • .060" (1.53mm) XLPE Insulation • PVC Inner Jacket • Black PVC Outer Jacket**

CSA C22.2#131 FT4 Flame Test	C5621	3	1291	1927	1.02	25.91	1.28	32.51	1.37	34.80	2316	10302	16.5	419.10
	C5622	4	1691	2524	1.12	28.45	1.38	35.05	1.48	37.59	3088	13736	17.7	449.58



Rip Cord

HAZ LOC
CSA C22.2#0.3 Clause 4.31 Low Acid Gas

XLPE = Cross-linked Polyethylene

Color Code: 2 conductors — Black, White (If required, a Red conductor can be used in place of White.)
 3 conductors — Black, Red, Blue (If required, a White conductor can be used in place of Blue.)
 4 conductors — Black, Red, Blue, White