

Line Level Analog Audio Cable

Single-Pair Cables



Description	Part No.	UL NEC/ C(UL) CEC Type	No. of Pairs	Color Code	Standard Lengths		Standard Unit Weight		Insulation Thickness		Jacket Thickness		Nominal OD		Nominal Capacitance			
					Ft.	m	Lbs.	kg	Inch	mm	Inch	mm	Inch	mm	* pF/ Ft.	* pF/ m	** pF/ Ft.	** pF/ m

16 AWG Stranded (19x29) Tinned Copper Conductors • Twisted Pair • Tinned Copper Spiral Wrapped Shield (85% Coverage)

PVC Insulation • Chrome PVC Jacket

300V RMS 60°C	8780	NEC:	1	Black,	500	152.4	23.5	10.7	.023	.58	.030	.76	.280	7.11	57	187	98	322
		CMG:		White	U-1000	U-304.8	44.0	20.0										
		CEC:			1000	304.8	46.0	20.9										
		CMG FT4																



16 AWG Stranded (19x29) TC Conductors • Twisted Pair • Overall Beldfoil® Shield (100% Coverage) • 18 AWG Stranded TC Drain Wire

Polyethylene Insulation • Chrome PVC Jacket

Low-Capacitance	8719	NEC:	1	Black,	U-500	U-152.4	24.0	10.9	.032	.81	.032	.81	.313	7.95	23	75	44	144
UL AWM Style 20253 (600V RMS 80°C)		CM, CL2		Clear	500	152.4	25.5	11.6										
		CEC:			U-1000	U-304.8	47.0	21.3										
		CM			1000	304.8	50.0	22.7										
					2000	609.6	100.0	45.5										
					5000	1524.0	245.0	111.4										
Shorting Fold					10000 [†]	3048.0	510.0	231.3										



14 AWG Stranded (19x27) TC Conductors • Twisted Pair • Overall Beldfoil Shield (100% Coverage) • 16 AWG Stranded TC Drain Wire

Polyethylene Insulation • Chrome PVC Jacket

Low-Capacitance	8720	NEC:	1	Black,	U-500	U-152.4	34.0	15.4	.032	.81	.035	.89	.355	9.02	24	79	47	154
UL AWM Style 20253 (600V RMS 80°C)		CL2		Clear	500	152.4	35.0	15.9										
					1000	304.8	71.0	32.3										
					2000	609.6	138.0	62.7										



12 AWG Stranded (19x25) TC Conductors • Twisted Pair • Overall Beldfoil Shield (100% Coverage) • 14 AWG Stranded TC Drain Wire

Polyethylene Insulation • Chrome PVC Jacket

Low-Capacitance	8718	NEC	1	Black,	U-500	U-152.4	47.5	21.6	.037	.94	.040	1.02	.400	10.16	25	82	49	161
UL AWM Style 20253 (600V RMS 80°C)		CL2		Clear	500	152.4	50.5	22.9										
					1000	304.8	100.0	45.5										
					2000	609.6	198.0	90.0										



TC = Tinned Copper

*Capacitance between conductors.

**Capacitance between one conductor and other conductors connected to shield.

[†] Final put-up length may vary -10% to +20% from length shown. May contain 2 pieces. Minimum length of any one piece is 1500 ft.