

## Speaker Wire and Cable

Electrolytic Tough Pitch (ETP) High-Conductivity Copper Speaker Cables  
Parallel Zip Constructions




Description	Part No.	UL NEC/ C(UL) CEC Type	No. of Cond.	Standard Lengths		Standard Unit Weight		Insulation Thickness		Nominal OD	
				Ft.	m	Lbs.	kg	Inch	mm	Inch	mm

**24 AWG** Stranded (7x32) ETP High-conductivity Copper Conductors • Parallel: (1) Tinned, (1) Bare

**PVC Insulation** (Available in Clear, White, Brown or Chrome)

300V 60°C (Clear)	<b>8782</b>	—	2	U-1000 <sup>▲</sup>	U-304.8	7.0	3.2	.017	.43	.058	1.47
300V 75°C (Chrome, Brown, White)				1000 <sup>♦</sup>	304.8	6.0	2.7			x	x
										.116	2.95



<sup>▲</sup>U-1000 ft. put-up available in Brown or Chrome only.

<sup>♦</sup>1000 ft. put-up available in White or Clear only.

**22 AWG** Stranded (7x30) ETP High-conductivity Copper Conductors • Parallel: (1) Tinned, (1) Bare

**Clear PVC Insulation**


300V 60°C	<b>9712</b>	—	2	1000	304.8	9.0	4.1	.017	.43	.065	1.65
										x	x
										.130	3.30



**20 AWG** Stranded (7x28) ETP High-conductivity Copper Conductors • Parallel: (1) Tinned, (1) Bare

**Clear or Chrome PVC Insulation**


300V 60°C (Clear)	<b>8649</b>	—	2	1000	304.8	12.0	5.5	.018	.46	.073	1.85
300V 75°C (Chrome)										x	x
VW-1										.146	3.71



**18 AWG** Stranded (16x30) ETP High-conductivity Copper Conductors • Parallel: (1) Tinned, (1) Bare

**Clear PVC Insulation**


300V 60°C	<b>9708</b>	—	2	U-500	U-152.4	11.0	5.0	.032	.81	.110	2.79
				500	152.4	10.5	4.8			x	x
				U-1000	U-304.8	21.0	9.5			.220	5.59
				1000	304.8	21.0	9.5				



**16 AWG** Stranded (26x30) ETP High-conductivity Copper Conductors • Parallel: (1) Tinned, (1) Bare

**Clear PVC Insulation**


300V 60°C	<b>9716</b>	—	2	U-1000	U-304.8	27.0	12.2	.027	.69	.115	2.92
				1000	304.8	26.0	11.8			x	x
										.230	5.84



**14 AWG** Stranded (19x27) ETP High-conductivity Copper Conductors • Parallel: (1) Tinned, (1) Bare

**Clear PVC Insulation**

300V 60°C	<b>9717</b>	—	2	U-1000	U-304.8	42.0	19.1	.035	.89	.146	3.71
				1000	304.8	42.0	19.1			x	x
										.292	7.42



**12 AWG** Stranded (65x30) ETP High-conductivity Copper Conductors • Parallel: (1) Tinned, (1) Bare

**Clear PVC Insulation**

300V 60°C	<b>9718</b>	—	2	500	152.4	33.0	15.0	.045	1.14	.185	4.70
				1000	304.8	66.0	30.0			x	x
										.370	9.40

