

## Speaker Wire and Cable

### High-Flex Multi-Conductor Cables

### Bi-amp and Tri-amp Speaker Connections




Description	Part No.	UL NEC/ C(UL) CEC Type	No. of Cond.	Color Code	Standard Lengths		Standard Unit Weight		Insulation Thickness		Jacket Thickness		Nominal OD	
					Ft.	m	Lbs.	kg	Inch	mm	Inch	mm	Inch	mm

**14 AWG** Stranded (104x34) Bare Copper Conductors • Conductors Cabled with Fillers • Paper Wrap


#### PVC Insulation • Overall Matte Black PVC Jacket

<b>High-Flex</b> 60°C	<b>1810A</b>	—	4	Red, Green, White, Black	250	76.2	26.3	11.9	.025	.64	.040	1.02	.390	9.91
					500	152.4	55.5	25.2						
					1000	304.8	114.0	51.7						



Compatible with Neutrik Speakon® Connectors.

<b>High-Flex</b> 60°C	<b>1811A</b>	—	8	Brown, Red, Orange, Yellow, Green, White, Blue, Black	1000	304.8	205.0	93.0	.025	.64	.040	1.02	.515	13.08	



Compatible with Neutrik Speakon® Connectors.

**10 AWG** Stranded (65x28) Bare High-conductivity ETP Copper Conductors • Highly Stranded for Ultra Flexibility • Rip Cord

#### High-grade PVC Insulation • PVC Jacket (Available in Gray)

<b>High-Flex</b> 75°C, UL 1581	<b>5T00UP</b>	NEC: CL2 Audio Use Only	2	Black, White	500	152.4	49.5	22.5	.020	.38	.026	.66	.356	9.04
					1000	304.8	96.0	49.5						



For Plenum version of 5T00UP, see 6T00UP.

Jacket sequentially marked at 2 ft. intervals.

**10 AWG** Stranded (65x28) Bare Copper Conductors • Cabled • Rip Cord

#### Plenum • Flamarrest® Insulation • Natural Flamarrest Jacket

<b>High-Flex</b> 150V 75°C	<b>6T00UP</b>	NEC: CL2P Audio Use Only	2	Black, White	1000	304.8	85.0	38.6	.011	.28	.015	.38	.308	7.82



Jacket sequentially marked at 2 ft. intervals.

Neutrik is a Liechtenstein Corporation trademark.

# BELDEN

For more information, contact Belden Technical Support: 1-800-BELDEN-1 • [www.belden.com](http://www.belden.com)

[Belden114@cablecon.kr](mailto:Belden114@cablecon.kr) / 0707-434-7704 / Fax. 02-744-0909 / [www.CableCon.co.kr](http://www.CableCon.co.kr)