

Special Application Audio, Communication and Instrumentation Cable

Microphone/Musical Instrument Cables



Description	Part No.	UL NEC/ C(UL) CEC Type	No. of Cond.	Color Code	Standard Lengths		Standard Unit Weight		Insulation Thickness		Jacket Thickness		Nominal OD		Nominal Capacitance			
					Ft.	m	Lbs.	kg	Inch	mm	Inch	mm	Inch	mm	* pF/ Ft.	* pF/ m	** pF/ Ft.	** pF/ m

Mic • 20 AWG Stranded (19x32) High-conductivity TC Conductors, Cabled • Rayon Braid • TC Braid Shield (84% Coverage)

Polyethylene Insulation • Chrome PVC Jacket

Low-Impedance	8405	—	5	Black,	250	46.2	14.8	6.7	.016	.41	.035	.89	.281	7.14	23	76	40	131
UL AWM Style 2094				Clear,	500	152.4	29.5	13.4										
(300V 60°C)				Green,	1000	304.8	63.0	28.6										
VW-1				Red,														
				Blue														



Mic • 20 AWG Stranded (26x34) High-conductivity TC Conductors, Cabled • Cotton Wrap • Rayon Braid • TC Braid Shield (85% Coverage)

Rubber Insulation • Black EPDM Rubber Jacket

Low-Impedance	8425	—	5	Blue,	100	30.5	7.8	3.5	.023	.58	.031	.79	.318	8.08	30	98	55	180
600V RMS 90°C				Orange,	250	46.2	17.3	7.8										
(60°C non-UL)				Black,														
				White,														
				Brown														
	8426	—	6	(Same as 8425)	100	30.5	9.0	4.1	.023	.58	.037	.94	.342	8.69	30	98	55	180
				+ Green	250	46.2	21.0	9.5										
	8427	—	7	(Same as 8426)	100	30.5	9.8	4.5	.023	.58	.041	1.04	.355	9.02	30	98	55	180
				+ Red	250	46.2	22.3	10.1										
	8418	—	8	(Same as 8427)	100	30.5	11.0	5.0	.023	.58	.037	.94	.381	9.68	30	98	55	180
				+ Yellow	250	46.2	25.0	11.3										

EPDM = Ethylene Propylene Diene Monomer • TC = Tinned Copper

*Capacitance between conductors.

**Capacitance between one conductor and other conductors connected to shield.