

**Multi-conductor and Paired Cable**

Less than 25 Conductors

No. of Conductors	Unshielded		Spiral Shield		Braid Shield		Overall Beldfoil®		Overall Foil/Braid		Individual Beldfoil		Individual Braid	
	Part No.	Page	Part No.	Page	Part No.	Page	Part No.	Page	Part No.	Page	Part No.	Page	Part No.	Page
<b>25 AWG and smaller</b>														
25	—	—	—	—	—	—	8142FO	5.14	9637 8142	4.16 5.27 19.57	—	—	—	—
26	—	—	—	—	—	—	—	—	9813	5.26	—	—	—	—
32	—	—	—	—	—	—	—	—	—	—	7893A <sup>■</sup>	19.28	7886A <sup>▶</sup>	19.17
36	—	—	—	—	—	—	8148FO	5.14	8148 9819	5.27 5.26	—	—	—	—
48	—	—	—	—	—	—	—	—	—	—	—	—	7887A <sup>▶</sup>	19.17
50	—	—	—	—	—	—	8155FO	5.14	9825 8155 1401A	5.26 5.27 15.82	—	—	—	—
62	—	—	—	—	—	—	—	—	9814	5.26	—	—	—	—
64	—	—	—	—	—	—	—	—	—	—	—	—	7888A <sup>▶</sup>	19.17
68	—	—	—	—	—	—	—	—	1403A	15.82	—	—	—	—
96	—	—	—	—	—	—	—	—	—	—	—	—	7889A <sup>▶</sup>	19.17
<b>24 AWG</b>														
25	—	—	—	—	—	—	9543 9684 1424A 82512 88112	4.11 5.15 5.15 5.49 5.50	9617 9937 8342 8112	4.17 4.18 5.29 5.31 19.57	—	—	—	—
30	—	—	—	—	—	—	9544 9515 1425A	4.11 5.12 5.15	8345 8115	5.29 5.31	9735	5.35 19.29	—	—
32	24501848	15.65	—	—	—	—	—	—	—	—	1412R <sup>■</sup> 1514C <sup>■</sup> 1850F <sup>■</sup>	19.18 19.19 19.28	1916A	19.20
34	—	—	—	—	—	—	—	—	—	—	9736	5.35 19.29	—	—
36	—	—	—	—	—	—	—	—	8348 9837 8118	5.29 5.30 5.31	8178 <sup>■</sup> 89758	5.45 5.53 19.30	—	—
37	—	—	—	—	—	—	88118	5.50	9618 9938	4.17 4.18	—	—	—	—
38	—	—	—	—	—	—	9519	5.12	—	—	9737	5.35 19.29	—	—
40	—	—	—	—	—	—	9545	4.11	—	—	1413R <sup>■</sup> 1515C <sup>■</sup>	19.18 19.19	—	—
48	1700S6 1701S6	15.55 15.55	—	—	—	—	—	—	—	—	1414R <sup>■</sup> 1516C <sup>■</sup> 1852F <sup>■</sup>	19.18 19.19 19.28	1924A	19.20
50	9585 <sup>▼</sup> 1864A <sup>▼</sup> 1871A <sup>▼</sup> 1232A1 <sup>▼</sup> 22713010 24501858 24571221 24572XXX 24576XXX 24577XXX 25500XXX	5.4 15.61 15.61 15.63 15.66 15.65 15.65 15.59 15.58 15.58 15.60	—	—	—	—	9546 9525 88125	4.11 5.12 5.50	9619 8355 9838 8125	4.17 5.29 5.30 5.31	9995 8185 <sup>■</sup>	5.37 5.45	—	—
52	—	—	—	—	—	—	—	—	—	—	1415R <sup>■</sup> 1517C <sup>■</sup>	19.18 19.19	—	—
54	—	—	—	—	—	—	—	—	—	—	9738	5.35 19.29	—	—
64	—	—	—	—	—	—	—	—	—	—	1416R <sup>■</sup> 1518C <sup>■</sup> 1854F <sup>■</sup>	19.18 19.19 19.28	1932A	19.20

▼ Solid conductors  
◆ Siamese version

\* Armored  
● Duofoil<sup>®</sup> shield

■ Individually shielded pairs or triads, plus overall foil, overall braid or overall foil and braid.

† Triad  
‡ Quad

**BELDEN**

For more information, contact Belden Technical Support: 1-800-BELDEN-1 • www.belden.com

Belden114@cablcon.kr / 0707-434-7704 / Fax. 02-744-0909 / www.CableCon.co.kr