

Security and Alarm Cable

Water-Blocked for Use in Underground Ducts



Water-blocked, Shielded Twisted Pair plus Conductor(s) CM FT1 Rated

Product Description

Tinned copper conductors, PVC insulation, Black/Red conductors twisted into a pair and shielded with Beldfoil® tape (aluminum side facing in) and drain wire, cabled with additional insulated conductor(s) as indicated, water-blocking tape overall, Gray PVC jacket with rip cord. Sequential footage marking every two feet.

Color Code: Black & Red (shielded pair);
White, Green, Brown, Blue.


Specifications

Conductor	Tinned Copper
Insulation	PVC
Insulation Thickness	.010" (.254mm)
Shield	
Twisted Pair	Beldfoil
Overall	Water-blocking Tape
Jacket	PVC
Approvals	
NEC	CM
CEC	CM FT1
NEC Articles	800
Voltage Rating	300V
Temperature Rating	105°C


Applications

- Security Systems
- Intercom/PA Systems
- Sound/Audio Systems
- Power-Limited Controls
- Indoor or Outdoor Use

Solid Conductor



Stranded Conductor



Part No.	No. of Pairs + No. of Cond.	Stranding	Standard Lengths		Standard Unit Weight		Outer Jacket Thickness		Nominal OD	
			Ft.	m	Lbs.	kg	Inch	mm	Inch	mm

Water-blocked, STP plus Conductor(s) (NEC CM and CEC CM FT1)

22 AWG										
5521G1	1 STP +1/C	solid	U-500	U-152	12.0	5.4	.025	.64	.212	5.38
			500	152	13.0	5.9				
			U-1000	U-305	22.0	10.0				
			1000	305	22.0	10.0				
5501G1	1 STP +1/C	7	U-500	U-152	12.0	5.4	.025	.64	.222	5.64
			500	152	12.0	5.4				
			U-1000	U-305	23.0	10.4				
			1000	305	25.0	11.4				
5522G1	1 STP +2/C	solid	U-500	U-152	13.0	6.0	.025	.64	.224	5.69
			500	152	15.0	6.8				
			U-1000	U-305	25.0	11.3				
			1000	305	27.0	12.3				
5502G1	1 STP +2/C	7	U-500	U-152	14.0	6.4	.025	.64	.240	6.10
			500	152	14.0	6.4				
			U-1000	U-305	27.0	12.3				
			1000	305	29.0	13.2				
5504G1	1 STP +4/C	7	U-500	U-152	18.0	8.2	.025	.64	.240	6.10
			500	152	18.5	8.4				
			U-1000	U-305	35.0	15.9				
			1000	305	37.0	16.8				

STP = Shielded Twisted Pair(s) • /C = Conductor(s)

Security Coaxial Cable

Surveillance and CCTV Applications

Shielded or Flooded for Use in Underground Ducts



Coax

CM FT1 Rated

Product Description

Bare copper conductor, foam polyethylene insulation, bare copper braid shield. Black PVC jacket. Sequential footage marking every two feet.

Water-blocked Coax

CM FT1 Rated

Product Description

Bare copper conductor, foam polyolefin insulation, foil plus braid shield as shown per item, braid impregnated with CoreGuard® flame retardant flooding compound, Black UV resistant PVC jacket. Sequential footage marking every two feet.

Specifications

Conductor	Bare Copper
Insulation	FPE
Shield	
Coax	Bare Copper Braid
Water-blocked Coax	Foil + Braid
Jacket	PVC
Approvals	
NEC	CM
CEC	CM FT1
NEC Articles	800
Nominal Impedance	75Ω
Temperature Rating	75°C


Applications

- CCTV
- Video Security Coax


Solid Conductor



Stranded Conductor



Water-blocked



CoreGuard

Part No.	AWG	Stranding and Conductor	Shield/Braid Coverage	Insulation Nominal OD		Nominal OD		Standard Lengths		Standard Unit Weight	
				Inch	mm	Inch	mm	Ft.	m	Lbs.	kg

Coax (NEC CM and CEC CM FT1)

Mini RG-59 Type

573945*	25	solid BC	94% BC	.085	2.16	.146	3.71	U-1000	U-305	15.0	6.8
								1000	305	14.0	6.4

RG-59 Type

551945	22	7/w BC	95% BC	.140	3.56	.232	5.89	U-1000	U-305	33.0	15.0
								1000	305	30.0	13.6

543945*	20	solid BC	95% BC	.145	3.68	.232	5.89	U-500	U-152	12.5	5.7
								500	152	13.0	6.0
								U-1000	U-305	25.0	11.3
								1000	305	31.0	14.1

RG-6 Type

533945*	18	solid BC	95% BC	.180	4.57	.266	6.76	500	152	21.0	9.5
								U-1000	U-305	40.0	18.1
								1000	305	41.0	18.6

RG-11 Type

513945	14	solid BC	95% BC	.280	7.11	.405	10.29	500	152	52.5	23.8
								1000	305	98.0	44.5

Water-blocked Coax (NEC CM and CEC CM FT1)

RG-59 Type

5439W5	20	solid BC	Duobond® II + 95% tinned copper braid	.145	3.68	.236	5.99	U-500	U-152	17.5	7.9
								500	152	17.5	7.9
								U-1000	U-305	34.0	15.4
								1000	305	34.0	15.4

RG-6 Type

5339W5	18	solid BC	Duofoil® + 60% aluminum braid	.180	4.57	.270	6.86	U-500	U-152	15.5	7.0
								500	152	15.5	7.0
								U-1000	U-305	30.0	13.6
								1000	305	30.0	13.6

BC = Bare Copper

*Available in other jacket colors. Consult www.belden.com.