

Security and Alarm Cable

Commercial Applications
Unshielded, Plenum-Rated



Unshielded Multi-conductor

CMP FT6 Rated

Product Description

Bare copper conductors, Flamarrest® insulation, conductors cabled, Natural Flamarrest jacket, rip cord. Sequential footage marking every two feet.

Color Code: See chart below.

Specifications

Conductor	Bare Copper
Insulation	Flamarrest
Insulation Thickness	.009" (.229mm)
Jacket	Flamarrest
Approvals	
NEC	CMP
CEC	CMP FT6
NEC Articles	800
Voltage Rating	300V
Temperature Rating	75°C

Applications

- Security Systems
- Intercom/PA Systems
- Sound/Audio Systems
- Power-Limited Controls

Solid Conductor



Stranded Conductor



Color Code Chart

Cond. No.	Color	Cond. No.	Color
1	Black	7	Orange
2	Red	8	Yellow
3	White	9	Purple
4	Green	10	Gray
5	Brown	11	Pink
6	Blue	12	Tan

Part No.	No. of Cond.	Stranding	Standard Lengths		Standard Unit Weight		Outer Jacket Thickness		Nominal OD	
			Ft.	m	Lbs.	kg	Inch	mm	Inch	mm

Unshielded Multi-conductor (NEC CMP and CEC CMP FT6)

22 AWG										
6520UE	2	solid	U-1000 1000	U-305 305	10.0 9.0	4.5 4.1	.015	.38	.118	3.00
6500UE	2	7	C-500 C-1000 U-1000 1000	C-152 C-305 U-305 305	4.5 9.0 10.0 10.0	2.0 4.1 4.5 4.5	.015	.38	.124	3.15
6521UE	3	solid	1000	305	13.0	5.9	.015	.38	.125	3.18
6501UE	3	7	U-1000 1000	U-305 305	14.0 13.0	6.4 5.9	.015	.38	.131	3.33
6522UE	4	solid	U-500 U-1000 1000	U-152 U-305 305	8.5 17.0 16.0	3.9 7.7 7.3	.015	.38	.136	3.45
6502UE	4	7	C-500 U-500 500 U-1000 1000	C-152 U-152 152 U-305 305	8.0 9.0 8.5 17.0 17.0	3.6 4.1 3.9 7.7 7.7	.015	.38	.143	3.63
6524UE	6	solid	C-500 U-1000	C-152 U-305	10.5 23.0	4.8 10.5	.015	.38	.162	4.11
6504UE	6	7	C-500 500 U-1000 1000	C-152 152 U-305 305	11.0 12.0 24.0 24.0	5.0 5.5 10.9 10.9	.015	.38	.171	4.34
6506UE	8	7	U-500 U-1000 1000	U-152 U-305 305	15.5 30.0 31.0	7.0 13.6 14.1	.015	.38	.186	4.72
6508UE	10	7	U-1000 1000	U-305 305	37.0 43.0	16.8 19.5	.015	.38	.218	5.54
6509UE	12	7	U-500 U-1000 1000	U-152 U-305 305	22.5 43.0 45.0	10.2 19.5 20.4	.015	.38	.225	5.72
20 AWG										
6400UE	2	7	C-500 500 U-1000 1000	C-152 152 U-305 305	6.0 7.0 14.0 14.0	2.7 3.2 6.4 6.4	.015	.38	.138	3.51
6401UE	3	7	U-1000 1000 5000	U-305 305 1524	19.0 18.0 90.0	8.6 8.2 40.9	.015	.38	.146	3.71
6402UE	4	7	U-1000 1000	U-305 305	24.0 24.0	10.9 10.9	.015	.38	.160	4.06
6403UE	5	7	U-1000 1000	U-305 305	28.0 28.0	12.7 12.7	.015	.38	.176	4.47
6406UE	8	7	1000	305	44.0	20.0	.015	.38	.209	5.31

Security and Alarm Cable

Commercial Applications
Unshielded, Plenum-Rated



Unshielded Multi-conductor (cont'd.)
CMP FT6 Rated

Product Description

Bare copper conductors, Flamarrest® insulation, conductors cabled, Natural Flamarrest jacket, rip cord. Sequential footage marking every two feet.

Color Code: See chart below.

Specifications

Conductor	Bare Copper
Insulation	Flamarrest
Insulation Thickness	.009" (.229mm)
Jacket	Flamarrest
Approvals	
NEC	CMP
CEC	CMP FT6
NEC Articles	800
Voltage Rating	300V
Temperature Rating	75°C

Applications

- Security Systems
- Intercom/PA Systems
- Sound/Audio Systems
- Power-Limited Controls

Solid Conductor



Stranded Conductor



Color Code Chart

Cond. No.	Color	Cond. No.	Color
1	Black	7	Orange
2	Red	8	Yellow
3	White	9	Purple
4	Green	10	Gray
5	Brown	11	Pink
6	Blue	12	Tan

Part No.	No. of Cond.	Stranding	Standard Lengths		Standard Unit Weight		Outer Jacket Thickness		Nominal OD	
			Ft.	m	Lbs.	kg	Inch	mm	Inch	mm

Unshielded Multi-conductor (NEC CMP and CEC CMP FT6)

18 AWG										
6320UE	2	solid	U-1000	U-305	17.0	7.7	.015	.38	.147	3.73
6300UE*	2	7	C-500	C-152	8.0	3.6	.015	.38	.157	3.99
			U-500	U-152	9.5	4.3				
			500	152	9.0	4.1				
			U-1000	U-305	18.0	8.2				
			1000	305	18.0	8.2				
5000	1520	90.0	40.8							
6321UE	3	solid	U-1000	U-305	24.0	10.9	.015	.38	.156	3.96
			1000	305	24.0	10.9				
6301UE	3	7	500	152	12.5	5.7	.015	.38	.168	4.27
			U-1000	U-305	25.0	11.4				
			1000	305	25.0	11.4				
6322UE	4	solid	U-1000	U-305	30.0	13.6	.015	.38	.171	4.34
6302UE	4	7	C-250	C-76	8.5	3.9	.015	.38	.186	4.72
			C-500	C-152	17.0	7.7				
			U-500	U-152	18.5	8.4				
			500	152	18.5	8.4				
			U-1000	U-305	36.0	16.4				
1000	305	39.0	17.7							
5000	1524	180.0	81.7							
6303UE	5	7	U-1000	U-305	39.0	17.7	.015	.38	.203	5.16
			1000	305	40.0	18.1				
6304UE	6	7	U-500	U-152	23.5	10.7	.015	.38	.222	5.64
			500	152	23.0	10.4				
			1000	305	51.0	23.2				
6306UE	8	7	500	152	30.5	13.9	.015	.38	.242	6.15
			1000	305	65.0	29.5				
6307UE	9	7	1000	305	68.0	30.9	.015	.38	.262	6.65
6308UE	10	7	1000	305	75.0	34.1	.015	.38	.286	7.26
6309UE	12	7	1000	305	84.0	38.2	.015	.38	.296	7.52
16 AWG										
6200UE	2	19	500	152	13.0	5.9	.015	.38	.180	4.57
			U-1000	U-305	25.0	11.3				
			1000	305	26.0	11.8				
6201UE	3	19	500	152	18.0	8.2	.015	.38	.191	4.85
			U-1000	U-305	36.0	16.4				
			1000	305	37.0	16.8				
6202UE	4	19	500	152	24.0	10.9	.015	.38	.211	5.36
			U-1000	U-305	46.0	20.9				
			1000	305	52.0	23.6				

*6300UE also available in Gray and Black.