

Security and Alarm Cable

Commercial Applications
Unshielded, Plenum-Rated



Unshielded Multi-conductor

CL2P Rated

Product Description

Bare copper conductors, Flamarrest® insulation, conductors cabled, Natural Flamarrest jacket, rip cord. Sequential footage marking every two feet.

Color Code: See chart below.

Specifications

Conductor	Bare Copper
Insulation	Flamarrest
Insulation Thickness	.011" (.279mm)
Jacket	Flamarrest
Approvals	
NEC	CL2P
NEC Articles	725
Voltage Rating	150V
Temperature Rating	75°C

Applications

- Security Systems
- Intercom/PA Systems
- Sound/Audio Systems
- Power-Limited Controls



Part No.	No. of Cond.	Stranding	Standard Lengths		Standard Unit Weight		Outer Jacket Thickness		Nominal OD	
			Ft.	m	Lbs.	kg	Inch	mm	Inch	mm

Unshielded Multi-conductor (NEC CL2P)

14 AWG										
6100UE	2	19	500	152	19.5	8.8	.015	.38	.222	5.64
			U-1000	U-305	38.0	17.2				
			1000	305	38.0	17.2				
			5000	1524	195.0	88.5				
6101UE	3	19	1000	305	56.0	25.4	.015	.38	.236	5.99
6102UE	4	19	1000	305	73.0	33.2	.015	.38	.261	6.63
12 AWG										
6000UE	2	19	500	152	32.0	14.5	.015	.38	.256	6.50
			1000	305	58.0	26.4				
6001UE	3	19	1000	305	83.0	37.7	.015	.38	.273	6.93
6002UE	4	19	1000	305	111.0	50.4	.018	.46	.308	7.82

Color Code Chart

Cond. No.	Color
1	Black
2	White
3	Red
4	Green