

## Security and Alarm Cable

Commercial Applications  
Unshielded



### Unshielded Multi-conductor CMR/CMG FT4 Rated

#### Product Description

Bare copper conductors, PVC insulation, Gray PVC jacket with rip cord. Sequential footage marking every two feet.

**Color Code:** See chart below.

#### Specifications

<b>Conductor</b>	Bare Copper
<b>Insulation</b>	PVC
<b>Insulation Thickness</b>	.010" (.254mm)
<b>Jacket</b>	PVC
<b>Approvals</b>	
NEC	CMR
CEC	CMG FT4
<b>NEC Articles</b>	800
<b>Voltage Rating</b>	300V
<b>Temperature Rating</b>	75°C


#### Applications

- Security Systems
- Intercom/PA Systems
- Sound/Audio Systems
- Power-Limited Controls
- Single Line Telephone

#### Solid Conductor



#### Stranded Conductor



#### Color Code Chart ††

Cond. No.	Color	Cond. No.	Color
1	Black	11	Pink
2	Red	12	Tan
3	White	13	White/Black
4	Green	14	White/Red
5	Brown	15	White/Green
6	Blue	16	White/Orange
7	Orange	17	White/Blue
8	Yellow	18	White/Brown
9	Purple	19	White/Yellow
10	Gray	20	White/Purple

††Except 5582UE which is Black, Red, Yellow, Green for use as station wire.

Part No.	No. of Cond.	Stranding	Standard Lengths		Standard Unit Weight		Outer Jacket Thickness		Nominal OD	
			Ft.	m	Lbs.	kg	Inch	mm	Inch	mm

#### Unshielded Multi-conductor (NEC CMR and CEC CMG FT4)

22 AWG										
5520UE	2	solid	C-500 U-500 C-1000 U-1000 1000	C-152 U-152 C-305 U-305 305	4.0 5.5 8.0 9.0 9.0	1.8 2.5 3.6 4.1 4.1	.015	.38	.122	3.10
5500UE	2	7	C-500 U-500 500 C-1000 U-1000 1000	C-152 U-152 152 C-305 U-305 305	4.0 5.5 5.5 8.0 10.0 9.0	1.8 2.5 2.5 3.6 4.5 4.1	.015	.38	.128	3.25
5501UE	3	7	U-1000 1000	U-305 305	13.0 13.0	5.9 5.9	.015	.38	.135	3.43
5522UE	4	solid	U-1000 1000	U-305 305	16.0 16.0	7.3 7.3	.015	.38	.141	3.58
5582UE*	4	solid	C-500 U-500 U-1000 1000	C-152 U-152 U-305 305	7.0 6.5 12.0 12.0	3.2 3.0 5.5 5.5	.015	.38	.141	3.58
5502UE**	4	7	C-500 U-500 U-1000 1000	C-152 U-152 U-305 305	7.5 9.0 16.0 16.0	3.4 4.1 7.3 7.3	.015	.38	.148	3.76
5503UE	5	7	U-1000 1000	U-305 305	20.0 20.0	9.1 9.1	.015	.38	.162	4.11
5524UE	6	solid	C-500 1000	C-152 305	10.5 22.0	4.8 10.0	.015	.38	.168	4.27
5504UE**	6	7	C-500 U-500 500 U-1000 1000	C-152 U-152 152 U-305 305	12.5 14.0 13.5 27.0 27.0	5.7 6.4 6.1 12.3 12.3	.015	.38	.177	4.50
5526UE	8	solid	1000	305	28.0	12.7	.015	.38	.182	4.62
5506UE	8	7	U-1000 1000	U-305 305	29.0 30.0	13.2 13.6	.015	.38	.192	4.88
5508UE	10	7	U-1000 1000	U-305 305	36.0 41.0	16.3 18.6	.015	.38	.226	5.74
5529UE	12	solid	U-1000 1000	U-305 305	40.0 42.0	18.1 19.1	.015	.38	.221	5.61
5509UE	12	7	U-500 U-1000 1000	U-152 U-305 305	21.5 42.0 47.0	9.8 19.1 21.4	.015	.38	.233	5.92
20 AWG										
5400UE	2	7	C-500 U-1000 1000	C-152 U-305 305	6.0 13.0 13.0	2.7 5.9 5.9	.015	.38	.142	3.61
5401UE	3	7	500 U-1000 1000	152 U-305 305	9.0 18.0 18.0	4.1 8.2 8.2	.015	.38	.150	3.81
5402UE	4	7	C-500 U-1000 1000	C-152 U-305 305	10.5 23.0 23.0	4.8 10.5 10.5	.015	.38	.165	4.19
5403UE	5	7	U-1000 1000	U-305 305	27.0 28.0	12.2 12.7	.015	.38	.181	4.60
5405UE	7	7	500 1000	152 305	19.0 40.0	8.6 18.2	.015	.38	.198	5.03
5406UE	8	7	U-1000 1000	U-305 305	41.0 43.0	18.6 19.5	.015	.38	.215	5.46
5407UE	9	7	1000	305	48.0	21.8	.015	.38	.233	5.92
5408UE	10	7	1000	305	53.0	24.1	.015	.38	.254	6.45
5409UE	12	7	1000	305	62.0	28.1	.015	.38	.262	6.65
540BUE	20	7	1000	305	110.0	49.9	.025	.64	.347	8.81

\* 5582UE also available in Beige, Brown or White.

\*\* 5502UE and 5504UE also available in White.

# Security and Alarm Cable

Commercial Applications

Unshielded



## Unshielded Multi-conductor (cont'd.)

CMR/CMG FT4 Rated

### Product Description

Bare copper conductors, PVC insulation, Gray PVC jacket with rip cord. Sequential footage marking every two feet.

**Color Code:** See chart below.

### Specifications

<b>Conductor</b>	Bare Copper
<b>Insulation</b>	PVC
<b>Insulation Thickness</b>	.010" (.254mm)
<b>Jacket</b>	PVC
<b>Approvals</b>	
NEC	CMR
CEC	CMG FT4
<b>NEC Articles</b>	800
<b>Voltage Rating</b>	300V
<b>Temperature Rating</b>	75°C


### Applications

- Addressable Fire Systems
- Data Circuits
- Monitor/Detection
- Control Circuits
- Initiating Circuits
- Notification Circuits

### Solid Conductor



### Stranded Conductor



### Color Code Chart

Cond. No.	Color	Cond. No.	Color
1	Black	11	Pink
2	Red	12	Tan
3	White	13	White/Black
4	Green	14	White/Red
5	Brown	15	White/Green
6	Blue	16	White/Orange
7	Orange	17	White/Blue
8	Yellow	18	White/Brown
9	Purple	19	White/Yellow
10	Gray	20	White/Purple

Part No.	No. of Cond.	Stranding	Standard Lengths		Standard Unit Weight		Outer Jacket Thickness		Nominal OD	
			Ft.	m	Lbs.	kg	Inch	mm	Inch	mm

### Unshielded Multi-conductor (NEC CMR and CEC CMG FT4)

18 AWG										
5320UE	2	solid	C-500 U-1000	C-152 U-305	7.5 17.0	3.4 7.7	.015	.38	.151	3.84
5300UE*	2	7	C-500 U-500 500 U-1000 1000	C-152 U-152 152 U-305 305	8.5 9.5 9.5 17.0 18.0	3.9 4.3 4.3 7.7 8.2	.015	.38	.161	4.09
5321UE	3	solid	U-1000 1000	U-305 305	23.0 23.0	10.4 10.4	.015	.38	.160	4.06
5301UE	3	7	500 U-1000 1000	152 U-305 305	12.5 25.0 25.0	5.7 11.3 11.3	.015	.38	.171	4.34
5322UE	4	solid	1000	305	30.0	13.6	.015	.38	.176	4.47
5302UE	4	7	C-250 U-500 500 U-1000 1000	C-76.2 U-152 152 U-305 305	7.5 16.5 16.0 32.0 32.0	3.4 7.5 7.3 14.5 14.5	.015	.38	.188	4.78
5303UE	5	7	500 U-1000 1000	152 U-305 305	20.5 39.0 39.0	9.3 17.7 17.7	.015	.38	.207	5.26
5304UE	6	7	500 U-1000 1000	152 U-305 305	26.0 51.0 52.0	11.8 23.2 23.6	.015	.38	.226	5.74
5305UE	7	7	U-1000 1000	U-305 305	51.0 52.0	23.2 23.6	.015	.38	.226	5.74
5306UE	8	7	500 1000	152 305	30.0 59.0	13.6 26.8	.015	.38	.248	6.30
5307UE	9	7	1000	305	66.0	30.0	.015	.38	.269	6.83
5308UE	10	7	500 1000	152 305	38.5 74.0	17.5 33.6	.015	.38	.294	7.47
5309UE	12	7	500 1000	152 305	47.5 90.0	21.6 40.9	.020	.51	.314	7.98
530BUE	20	7	1000	305	152.0	69.0	.025	.64	.400	10.16
16 AWG										
5200UE	2	19	C-500 U-500 500 U-1000 1000	C-152 U-152 152 U-305 305	11.5 13.0 12.5 24.0 25.0	5.2 5.9 5.7 10.9 11.4	.015	.38	.184	4.67
5201UE	3	19	U-500 500 U-1000 1000	U-152 152 U-305 305	18.5 18.0 35.0 38.0	8.4 8.2 15.9 17.3	.015	.38	.196	4.98
5202UE	4	19	U-500 500 U-1000 1000	U-152 152 U-305 305	23.5 23.0 45.0 47.0	10.7 10.4 20.4 21.3	.015	.38	.216	5.49
5205UE	7	19	1000	305	77.0	35.0	.015	.38	.261	6.63

\*5300UE also available in White or Black.