


## Speaker Cable

### High-Strand Multi-conductor Audio Cables


Description	Part No.	UL NEC/ C(UL) CEC Type	No. of Cond.	Color Code	Standard Lengths		Standard Unit Weight		Insulation Thickness		Outer Jacket Thickness		Nominal OD	
					Ft.	m	Lbs.	kg	Inch	mm	Inch	mm	Inch	mm

**High-Strand • 16 AWG** Stranded (65x34) Bare High-conductivity ETP Copper Conductors • Highly Stranded for Ultra Flexibility • Rip Cord

**High-Grade PVC Insulation • PVC Jacket** (Available in Blue, Green, White, Black or Gray)

75°C  Rip Cord	<b>5200UP</b>	NEC: CM	2	Black, White	U-500	U-152.4	14.5	6.6	.015	.38	.015	.38	.208	5.28
					500	152.4	14.5	6.6						
					U-1000	U-304.8	28.0	12.7						
					1000	304.8	28.0	12.7						


Jacket sequentially marked at 2 ft. intervals.

75°C  Rip Cord	<b>5202UP</b>	NEC: CM	4	Black, White, Red, Green	U-500	U-152.4	25.5	11.6	.015	.38	.015	.38	.244	6.20
					500	152.4	26.0	11.8						
					U-1000	U-304.8	49.0	22.2						
					1000	304.8	51.0	23.2						

Jacket sequentially marked at 2 ft. intervals.

**High-Strand • 14 AWG** Stranded (42x30) Bare High-conductivity ETP Copper Conductors • Highly Stranded for Ultra Flexibility • Rip Cord


**High-Grade PVC Insulation • PVC Jacket** (Available in Blue, Green, White, Black or Gray)

75°C  Rip Cord	<b>5100UP</b>	NEC: CL3	2	Black, White	U-500	U-152.4	21.0	9.5	.020	.51	.015	.38	.260	6.60
					500	152.4	22.5	10.2						
					U-1000	U-304.8	41.0	18.6						
					1000	304.8	43.0	19.5						

Jacket sequentially marked at 2 ft. intervals.

**High-Strand • 12 AWG** Stranded (65x30) Bare High-conductivity ETP Copper Conductors • Highly Stranded for Ultra Flexibility • Rip Cord


**High-Grade PVC Insulation • PVC Jacket** (Available in Blue, Green, White, Black or Gray)

75°C  Rip Cord	<b>5000UP</b>	NEC: CL3	2	Black, White	U-500	U-152.4	31.0	14.1	.020	.51	.018	.46	.302	7.67
					500	152.4	32.5	14.7						
					1000	304.8	64.0	29.1						

Jacket sequentially marked at 2 ft. intervals.

**High-Strand • 10 AWG** Stranded (65x28) Bare High-conductivity ETP Copper Conductors • Highly Stranded for Ultra Flexibility

**High-Grade PVC Insulation • Gray PVC Jacket**

75°C  Rip Cord	<b>5T00UP</b>	NEC: CL2 Audio Use Only	2	Black, White	500	152.4	49.5	22.5	.020	.51	.026	.66	.356	9.04
					1000	304.8	96.0	43.6						

Jacket sequentially marked at 2 ft. intervals.