

Hypalon®

UL AWM Style 3191 600V, 105°C (CSA Type CL1053)

Product Description

This insulation is chlorosulfonated polyethylene. Hypalon insulation has excellent heat resistance, color stability and electrical properties. Hypalon is recommended for motor leads for Class 130(B) insulation systems. It may be considered as an alternative to Silicone rubber to withstand 155°C varnish baking temperatures, but is not suitable for operating temperatures above Class 130(B).

Recommended maximum baking cycles:
24 hours @ 300°F (149°C)



Stranded tinned copper conductor

UL AWM Style 3191, 3192, 3193 600V, 105°C (CSA Type CL1052, 300V)

Product Description

This insulation is chlorosulfonated polyethylene. Hypalon insulation has excellent heat resistance, color stability and electrical properties. Hypalon is recommended for motor leads for Class 130(B) insulation systems. It may be considered as an alternative to Silicone rubber to withstand 155°C varnish baking temperatures, but is not suitable for operating temperatures above Class 130(B).

Recommended maximum baking cycles:
24 hours @ 300°F (149°C)

Stranded Conductor



Stranded tinned copper conductor

Separator Over Conductor



Separator

Hypalon is a DuPont trademark.

Part No.	AWG (stranding) [sq. mm] (stranding in mm)	Insulation Thickness		Nominal OD		Standard Lengths		Standard Unit Weight		Stock Colors (See Color Codes Chart on Page 3.29)
		Inch	mm	Inch	mm	Ft.	m	Lbs.	kg	

600V, 105°C (UL & CSA)

UL AWM Style 3191 • CSA Type CL1053										
34418	18 (16x30) [.81 (16x.25)]	.045	1.14	.142	3.61	100 [†]	30.5	2.3	1.0	2, 10
						500 ^{††}	152.4	8.0	3.6	2, 4, 5, 8-10, 13
						5000 ^{†††}	1524.0	75.0	34.1	2, 5, 8, 10
34416	16 (26x30) [1.32 (26x.25)]	.045	1.14	.155	3.94	100 [†]	30.5	2.8	1.3	2, 10
						500 ^{††}	152.4	10.5	4.8	2, 4, 5, 8-10, 13
						4000 ^{†††}	1219.2	84.0	38.1	8, 10
34414	14 (41x30) [2.08 (41x.25)]	.045	1.14	.170	4.32	100 [†]	30.5	3.7	1.7	2, 8, 10
						500 ^{††}	152.4	14.0	6.4	2, 5, 8, 10
						4000 ^{†††}	1219.2	108.0	49.1	8, 10
34412	12 (65x30) [3.29 (65x.25)]	.045	1.14	.190	4.83	100 [†]	30.5	4.6	2.1	2, 8, 10
						500 ^{††}	152.4	17.5	7.9	2, 5, 8, 10, 13
						3000 ^{†††}	914.4	114.0	51.8	10

[†]100 ft. put-ups are one piece, exact. ^{††}250 ft. and 500 ft. put-ups are exact, may contain 2 pieces max. Min. length 50 ft.

^{†††}May contain more than one piece. Minimum length of any one piece is 200 ft.

600V, 105°C (UL) • 300V, 105°C (CSA)

UL AWM Style 3191 • CSA Type CL1052**										
34410	10 (65x28) [5.23 (65x.32)]	.045	1.14	.209	5.31	100 [†]	30.5	6.0	2.7	8, 10
						500 ^{††}	152.4	24.5	11.2	8, 10
						2000 ^{†††}	609.6	102.0	46.3	8, 10
UL AWM Style 3192 • CSA Type CL1052**										
34408*	8 (84x27) [8.60 (84x.36)]	.060	1.52	.290	7.37	100 [†]	30.5	9.4	4.3	8, 10
						250 ^{††}	76.2	24.8	11.2	8, 10
34406*	6 (84x25) [13.66 (84x.46)]	.060	1.52	.343	8.71	100 [†]	30.5	13.7	6.2	8, 10
						250 ^{††}	76.2	32.3	14.7	10
						1000 ^{†††}	304.8	136.0	61.8	10
34404*	4 (105x24) [21.53 (105x.51)]	.060	1.52	.399	10.14	100 [†]	30.5	19.1	8.7	8, 10
						250 ^{††}	76.2	51.0	23.2	10
						500 ^{††}	152.4	97.0	44.1	10
34403*	3 (133x24) [27.28 (133x.51)]	.060	1.52	.420	10.69	500 ^{††}	152.4	118.0	53.6	10
34402*	2 (163x24) [33.43 (163x.51)]	.060	1.52	.454	11.53	100 [†]	30.5	30.3	13.8	8, 10
						250 ^{††}	76.2	70.8	32.2	10
						500 ^{††}	152.4	139.0	63.2	10
UL AWM Style 3193 • CSA Type CL1052**										
34401*	1 (210x24) [43.07 (210x.51)]	.080	2.03	.557	14.15	50 [†]	15.2	18.4	8.4	10
						100 [†]	30.5	43.0	19.5	8, 10
						250 ^{††}	76.2	97.0	44.1	10
34490*	1/0 (262x24) [53.73 (262x.51)]	.080	2.03	.607	15.42	50 [†]	15.2	22.5	10.3	8, 10
						100 [†]	30.5	48.9	22.2	10
						250 ^{††}	76.2	114.8	52.2	10
34400*	2/0 (504x26) [67.85 (504x.41)]	.080	2.03	.668	16.97	50 [†]	15.2	27.6	12.6	8
						100 [†]	30.5	57.9	26.3	10
						250 ^{††}	76.2	139.5	63.4	10
34430*	3/0 (630x26) [84.81 (630x.41)]	.080	2.03	.732	18.59	50 [†]	15.2	38.5	17.5	10
						250 ^{††}	76.2	175.8	79.9	10
34440*	4/0 (805x26) [108.37 (805x.41)]	.080	2.03	.819	20.80	50 [†]	15.2	47.5	21.5	8, 10
						250 ^{††}	76.2	215.0	97.7	10

*Separator over conductor. **CSA requires additional wall thickness in sizes 10 AWG and larger to meet CL1053 requirements.

[†]50 and 100 ft. put-ups are one piece, exact. ^{††}250 and 500 ft. put-ups are exact, may contain 2 pieces max. Min. length 50 ft.

^{†††}1000 ft. put-ups exact, may contain 3 pieces max. Minimum length of any one piece is 50 ft.

*May contain more than one piece. Minimum length of any one piece is 200 ft.



For more information, contact **Belden Technical Support: 1-800-BELDEN-1 • www.belden.com**

Belden114@cablcon.kr / 0707-434-7704 / Fax. 02-744-0909 / www.CableCon.co.kr

Hypalon®

UL AWM Style 3190 300V, 105°C (CSA Type CL1052)

Product Description

This insulation is chlorosulfonated polyethylene. Hypalon insulation has excellent heat resistance, color stability and electrical properties. Hypalon is recommended for motor leads for Class 130(B) insulation systems. It may be considered as an alternative to Silicone rubber to withstand 155°C varnish baking temperatures, but is not suitable for operating temperatures above Class 130(B).



Stranded tinned copper conductor

5000V High-Voltage Hypalon

Product Description

This insulation is chlorosulfonated polyethylene. Hypalon insulation has excellent heat resistance, color stability and electrical properties.



Separator
Stranded tinned copper conductor

Part No.	AWG (stranding) [sq. mm] (stranding in mm)	Insulation Thickness		Nominal OD		Standard Lengths		Standard Unit Weight		Stock Colors (See Color Codes Chart on Page 3.29)
		Inch	mm	Inch	mm	Ft.	m	Lbs.	kg	

300V, 105°C (UL & CSA)

UL AWM Style 3190 • CSA Type CL1052

34922	22 (7x30) [.36 (7x.25)]	.030	.76	.093	2.36	5000 ^{††}	1524.0	35.0	15.9	10
34920	20 (10x30) [.51 (10x.25)]	.030	.76	.100	2.54	5000 ^{††}	1524.0	45.0	20.5	8, 10
34918	18 (16x30) [.81 (16x.25)]	.030	.76	.110	2.79	500 [†]	152.4	6.0	2.7	2, 4, 10
						5000 ^{††}	1524.0	55.0	25.0	2, 10
34916	16 (26x30) [1.32 (26x.25)]	.030	.76	.123	3.12	500 [†]	152.4	8.0	3.6	2, 9, 10
						5000 ^{††}	1524.0	80.0	36.4	10
34914	14 (41x30) [2.08 (41x.25)]	.030	.76	.138	3.51	*	*	*	*	Special Order*

*Contact Belden's Customer Service Department for order requirements. **1-800-BELDEN-1**.

[†]May contain more than one piece. Minimum length of any one piece is 50 ft.

^{††}May contain more than one piece. Minimum length of any one piece is 200 ft.

5000V

High-Voltage

36108	8 (84x27) [8.60 (84x.36)]	.150	3.81	.480	12.19	50 [▲]	15.2	7.9	3.6	10
						500 [•]	152.4	86.5	39.3	10
36106	6 (84x25) [13.66 (84x.46)]	.150	3.81	.532	13.51	50 [▲]	15.2	10.5	4.8	10
						500 [•]	152.4	113.5	51.6	10
36104	4 (105x24) [21.53 (105x.51)]	.150	3.81	.588	14.94	50 [▲]	15.2	13.9	6.3	10
						500 [•]	152.4	148.0	67.3	10
36102	2 (163x24) [33.43 (163x.51)]	.150	3.81	.643	16.33	50 [▲]	15.2	22.4	10.2	10
						500 [•]	152.4	194.0	88.2	10
36101	1 (210x24) [43.07 (210x.51)]	.150	3.81	.700	17.78	50 [▲]	15.2	26.4	12.0	10
						250 [•]	76.2	121.8	55.3	10
36190	1/0 (262x24) [53.73 (262x.51)]	.150	3.81	.750	19.05	50 [▲]	15.2	32.4	14.7	10
						500 [•]	152.4	287.5	130.7	10
36100	2/0 (504x26) [67.85 (504x.41)]	.150	3.81	.815	20.70	50 [▲]	15.2	37.5	17.0	10
36140	4/0 (805x26) [108.37 (805x.41)]	.150	3.81	.959	24.36	50 [▲]	15.2	52.5	23.8	10
						250 [•]	76.2	247.5	112.5	10

[▲]50 ft. put-ups are one piece, exact.

[•]250 ft. and 500 ft. put-ups are exact, but may contain 2 pieces max. Minimum length of any one piece is 50 ft.

Hypalon is a DuPont trademark.

BELDEN

For more information, contact **Belden Technical Support: 1-800-BELDEN-1 • www.belden.com**

Belden114@cablcon.kr / 0707-434-7704 / Fax. 02-744-0909 / www.CableCon.co.kr