



**Unshielded**

Antenna Rotor Control Cables, Security/Audio Systems  
and Duplex Primary Wire


Description	Part No.	UL NEC/ C(UL) CEC Type	No. of Cond.	Color Code	AWG (stranding)	Standard Lengths		Standard Unit Weight		Insulation Thickness		Jacket Thickness		Nominal OD	
						Ft.	m	Lbs.	kg	Inch	mm	Inch	mm	Inch	mm

**Antenna Rotor Cables** Stranded Tinned Copper Conductors • Conductors Cabled**PVC Insulation • Chrome PVC Jacket**


UL AWM Style 2464 (300V 80°C) VW-1 	<b>9405</b>	NEC: CM	8	Black, White	2@16 (19x28)	500	152.4	47.0	21.3	.019	.48	.032	.81	.345	8.76
				Brown, Red, Yellow, Blue, Orange, Green	6@18 (16x30)	1000	304.8	92.0	41.8			.018	.46		

UL AWM Style 2576 (150V 80°C) VW-1 	<b>8448</b>	NEC: CMG CEC: CMG FT4	8	Black, White	2@18 (16x30)	U-500	U-152.4	25.0	11.4	.019	.48	.032	.81	.259	6.58
				Red, Green, Brown, Blue, Yellow, Orange	6@22 (7x30)	U-1000	U-304.8	49.0	22.2			.010	.25		

**Security/Audio/Power Limited Controls Cable** Stranded Bare Copper Conductors • Conductors Parallel**PVC Insulation • Chrome PVC Jacket**

200V RMS 75°C VW-1 	<b>8484</b>	—	4	Black, Green, Red, White	20 (7x28)	U-500	U-152.4	12.5	5.7	—	—	—	—	.177	4.50
						U-1000	U-304.8	24.0	10.9						

**Duplex Primary Wire** Stranded Bare Copper Conductors • Conductors Parallel**PVC Insulation • Chrome PVC Jacket**

300V RMS 75°C VW-1 	<b>8677</b>	—	2	Brown, Red	16 (19x29)	500	152.4	18.5	8.4	.024	.61	.022	.56	.149	3.78
														.254	6.45
	<b>8675</b>	—	2	Brown, Red	14 (19x27)	500	152.4	23.5	10.7	.023	.58	.023	.58	.168	4.27
														x	x
														.290	7.37
	<b>8673</b>	—	2	Brown, Red	12 (19x25)	500	152.4	32.5	14.8	.026	.66	.022	.56	.186	4.72
														x	x
														.328	8.33
	<b>8678</b>	—	2	Brown, Red	10 (19x23)	500	152.4	51.0	23.1	.031	.79	.025	.64	.225	5.72
														x	x
														.400	10.16