


Unshielded

Power and Control Cables

Rubber and Oil-Resistant Rubber SO Cables

Description	Part No.	UL NEC/ C(UL) CEC Type	No. of Cond.	Color Code	Standard Lengths		Standard Unit Weight		Insulation Thickness		Jacket Thickness		Nominal OD		
					Ft.	m	Lbs.	kg	Inch	mm	Inch	mm	Inch	mm	
16 AWG Stranded (65x34) Bare Copper Conductors • Conductors Cabled with Fillers • Paper Tape Separator															
EPDM Rubber Insulation • Black Oil-resistant Rubber Jacket															
600V RMS 60°C CSA FT2 	9420	UL:	5	See	100	30.5	13.3	6.0	.033	.838	.084	2.13	.506	12.85	
		SO		Chart 2	500	152.4	73.5	33.4							
		CSA: SO		(Tech Info Section)	1000	304.8	143.0	65.0							
		9422	UL:	7	See	100	30.5	18.5	8.4	.033	.838	.083	2.11	.581	14.76
			SO		Chart 2	500	152.4	101.0	45.9						
			CSA: SO		(Tech Info Section)	1000	304.8	201.0	91.3						
	9424	UL:	9	See	100	30.5	29.6	13.4	.033	.838	.100	2.54	.720*	18.29	
		SO		Chart 2	500	152.4	150.5	68.3							
		CSA: SO		(Tech Info Section)	1000	304.8	288.0	130.8							
	9425	UL:	12	See	100	30.5	32.6	14.8	.033	.838	.100	2.54	.720	18.29	
		SO		Chart 2	500	152.4	165.5	75.1							
		CSA: SO		(Tech Info Section)	1000	304.8	318.0	144.4							
	9427	UL:	16	See	100	30.5	39.5	17.9	.033	.838	.100	2.54	.787	19.99	
		SO		Chart 2	1000	304.8	428.0	194.3							
		CSA: SO		(Tech Info Section)											
	9429	UL:	20	See	100	30.5	48.4	22.0	.033	.838	.100	2.54	.862	21.89	
		SO		Chart 2	500	152.4	233.0	105.8							
		CSA: SO		(Tech Info Section)											

EPDM = Ethylene Propylene Diene Monomer

*Fillers added in the center