


Overall Beldfoil® Shield

Low-Capacitance Computer Cables for EIA RS-232 and EIA RS-485 Applications

Description	Part No.	UL NEC/ C(UL) CEC Type	No. of Pairs	Color Code	Standard Lengths		Standard Unit Weight		Nom. DCR		Nominal OD		Nom. Imp. (Ω)	Nom. Vel. of Prop.	Nom. Capacitance			
					Ft.	m	Lbs.	kg	Cond.	Shield	Inch	mm			* pF/ Ft.	* pF/ m	** pF/ Ft.	** pF/ m
28 AWG Stranded (7x36) TC Conductors • Twisted Pairs • Overall Beldfoil Shield (100% Coverage) • 28 AWG Stranded TC Drain Wire																		
Datalene® Insulation • Chrome PVC Jacket																		
 <p>Z-Fold®</p>	UL AWM Style 2919 (30V 80°C)	8132FO	NEC: CL2	2	See Chart 5 (Tech Info Section)	500 1000	152.4 304.8	8.5 20.0	3.9 9.1	65.0Ω/M' 213.0Ω/km	23.1Ω/M' 75.8Ω/km	.215 5.46	120	78%	11.0	36.1	20.0	65.6
	8133FO	NEC: CL2	3	See Chart 5 (Tech Info Section)	500 1000	152.4 304.8	11.0 20.0	5.0 9.1	65.0Ω/M' 213.0Ω/km	23.1Ω/M' 75.8Ω/km	.250 6.35	120	78%	11.0	36.1	20.0	65.6	
	8134FO	NEC: CL2	4	See Chart 5 (Tech Info Section)	500 1000	152.4 304.8	13.5 31.0	6.1 14.1	65.0Ω/M' 213.0Ω/km	20.0Ω/M' 65.6Ω/km	.270 6.86	120	78%	11.0	36.1	20.0	65.6	
	8135FO	NEC: CL2	5	See Chart 5 (Tech Info Section)	500 1000	152.4 304.8	14.0 32.0	6.4 14.5	65.0Ω/M' 213.0Ω/km	20.0Ω/M' 65.6Ω/km	.280 7.11	120	78%	11.0	36.1	20.0	65.6	
	8138FO	NEC: CL2	8	See Chart 5 (Tech Info Section)	500 1000	152.4 304.8	22.0 42.0	10.0 19.1	65.0Ω/M' 213.0Ω/km	17.7Ω/M' 58.1Ω/km	.310 7.88	120	78%	11.0	36.1	20.0	65.6	
	8142FO	NEC: CL2	12.5 (12 pairs + 1 single)	See Chart 5 (Tech Info Section)	500 1000	152.4 304.8	27.5 54.0	12.5 24.5	65.0Ω/M' 213.0Ω/km	17.7Ω/M' 58.1Ω/km	.385 9.78	120	78%	11.0	36.1	20.0	65.6	
	8148FO	NEC: CL2	18	See Chart 5 (Tech Info Section)	500 1000	152.4 304.8	38.5 77.0	17.5 35.0	65.0Ω/M' 213.0Ω/km	15.8Ω/M' 51.8Ω/km	.445 11.31	120	78%	11.0	36.1	20.0	65.6	
	8155FO	NEC: CL2	25	See Chart 5 (Tech Info Section)	500 1000	152.4 304.8	42.0 84.0	19.1 38.2	65.0Ω/M' 213.0Ω/km	14.3Ω/M' 47.7Ω/km	.545 13.85	120	78%	11.0	36.1	20.0	65.6	

DCR = DC Resistance • TC = Tinned Copper


*Capacitance between conductors.

**Capacitance between one conductor and other conductors connected to shield.

Datalene insulation features include low dielectric constant and a dissipation factor for high-speed, low-distortion data handling. Physical properties include good crush resistance and light weight.

Overall Foil/Braid Shield

Low-Capacitance Computer Cables for EIA RS-232 and EIA RS-485 Applications

Description	Part No.	UL NEC/ C(UL) CEC Type	No. of Pairs	Color Code	Standard Lengths		Standard Unit Weight		Nom. DCR		Nominal OD		Nom. Imp. (Ω)	Nom. Vel. of Prop.	Nom. Capacitance			
					Ft.	m	Lbs.	kg	Cond.	Shield	Inch	mm			* pF/ Ft.	* pF/ m	** pF/ Ft.	** pF/ m
28 AWG Stranded (7x36) TC Conductors • Overall Beldfoil® (100% Coverage) + TC Braid Shield (65% Coverage) • 28 AWG Stranded TC Drain Wire																		
Datalene® Insulation • Chrome PVC Jacket																		
 <p>Shorting Fold</p>	8132	NEC: CL2	2	See Chart 5 (Tech Info Section)	100	30.5	3.6	1.6	65.0Ω/M'	5.1Ω/M'	.220	5.59	120	78%	11.0	36.1	20.0	65.6
					500	152.4	14.5	6.6	213.0Ω/km	16.6Ω/km								
					1000	304.8	29.0	13.2										
	8133	NEC: CL2	3	See Chart 5 (Tech Info Section)	100	30.5	3.8	1.7	65.0Ω/M'	5.2Ω/M'	.270	6.86	120	78%	11.0	36.1	20.0	65.6
					500	152.4	15.0	6.8	213.0Ω/km	17.1Ω/km								
					1000	304.8	34.0	15.5										
	8134	NEC: CL2	4	See Chart 5 (Tech Info Section)	100	30.5	4.3	2.0	65.0Ω/M'	4.4Ω/M'	.290	7.37	120	78%	11.0	36.1	20.0	65.6
					500	152.4	18.0	8.2	213.0Ω/km	14.3Ω/km								
					1000	304.8	39.0	17.7										
	8135	NEC: CL2	5	See Chart 5 (Tech Info Section)	100	30.5	4.6	2.1	65.0Ω/M'	4.2Ω/M'	.300	7.62	120	78%	11.0	36.1	20.0	65.6
500					152.4	21.0	9.1	213.0Ω/km	13.8Ω/km									
1000					304.8	42.0	18.2											
8138	NEC: CL2	8	See Chart 5 (Tech Info Section)	100	30.5	5.6	2.5	65.0Ω/M'	3.7Ω/M'	.330	8.38	120	78%	11.0	36.1	20.0	65.6	
				500	152.4	27.0	12.3	213.0Ω/km	12.3Ω/km									
				1000	304.8	52.0	23.6											
8142	NEC: CL2	12.5 (12 pairs + 1 single)	See Chart 5 (Tech Info Section)	100	30.5	6.8	3.1	65.0Ω/M'	3.1Ω/M'	.375	9.53	120	78%	11.0	36.1	20.0	65.6	
				500	152.4	33.0	15.0	213.0Ω/km	10.1Ω/km									
				1000	304.8	66.0	29.9											
8148	NEC: CL2	18	See Chart 5 (Tech Info Section)	100	30.5	8.5	3.9	65.0Ω/M'	2.6Ω/M'	.465	11.81	120	78%	11.0	36.1	20.0	65.6	
				500	152.4	47.5	21.6	213.0Ω/km	8.4Ω/km									
				1000	304.8	92.0	41.8											
8155	NEC: CL2	25	See Chart 5 (Tech Info Section)	100	30.5	11.1	5.0	65.0Ω/M'	2.3Ω/M'	.565	14.35	120	78%	11.0	36.1	20.0	65.6	
				500	152.4	64.0	29.1	213.0Ω/km	7.6Ω/km									
				1000	304.8	121.0	55.0											

DCR = DC Resistance • TC = Tinned Copper










*Capacitance between conductors.

**Capacitance between one conductor and other conductors connected to shield.

Datalene insulation features include low dielectric constant and a dissipation factor for high-speed, low-distortion data handling. Physical properties include good crush resistance and light weight.

Overall Foil/Braid Shield

Low-Capacitance Computer Cables for EIA RS-485 Applications
Plenum-Rated and Non-Plenum


Description	Part No.	UL NEC/ C(UL) CEC Type	No. of Pairs	Color Code	Standard Lengths		Standard Unit Weight		Nom. DCR		Nominal OD		Nom. Imp. (Ω)	Nom. Vel. of Prop.	Nom. Capacitance									
					Ft.	m	Lbs.	kg	Cond.	Shield	Inch	mm			* pF/ Ft.	* pF/ m	** pF/ Ft.	** pF/ m						
24 AWG Stranded (7x32) TC Conductors • Overall Beldfoil® (100% Coverage) + TC Braid Shield (90% Coverage) • 24 AWG Stranded TC Drain Wire																								
Polyethylene Insulation • Chrome PVC Jacket																								
UL AWM Style 2919 (30V 80°C) DMX 512 	9841	NEC:	1	See	100	30.5	4.3	2.0	24.0Ω/M'	3.4Ω/M'	.232	5.89	120	66%	12.8	42.0	23.0	75.5						
		CM		Chart 5	500	152.4	20.0	9.1	78.7Ω/km	11.0Ω/km	For Plenum versions of 9841, see 82841 or 89841.													
		CEC:		(Tech Info	1000	304.8	40.0	18.2																
		CM		Section)																				
	9842	NEC:	2	See	100	30.5	5.8	2.6	24.0Ω/M'	2.2Ω/M'	.340	8.64	120	66%	12.8	42.0	23.0	75.5						
		CM		Chart 5	500	152.4	29.5	13.4	78.7Ω/km	7.2Ω/km	For Plenum versions of 9842, see 82842.													
		CEC:		(Tech Info	1000	304.8	57.0	25.9																
		CM		Section)																				
	9843	NEC:	3	See	100	30.5	7.1	3.2	24.0Ω/M'	2.3Ω/M'	.360	9.14	120	66%	12.8	42.0	23.0	75.5						
		CM		Chart 5	500	152.4	34.5	15.7	78.7Ω/km	7.7Ω/km														
		CEC:		(Tech Info	1000	304.8	67.0	30.5																
		CM		Section)																				
	9844	NEC:	4	See	500	152.4	43.0	19.5	24.0Ω/M'	2.1Ω/M'	.390	9.91	120	66%	12.8	42.0	23.0	75.5						
		CM		Chart 5	1000	304.8	83.0	37.7	78.7Ω/km	6.9Ω/km														
		CEC:		(Tech Info																				
		CM		Section)																				
Plenum • Foam FEP Insulation • Natural Flamarrest® Jacket																								
300V RMS 	82841	NEC:	1	See	500	152.4	13.0	6.0	24.0Ω/M'	3.1Ω/M'	.204	5.18	120	76%	12	39.4	22	72.2						
		CMP		Chart 5	1000	304.8	26.0	11.8	78.7Ω/km	10.2Ω/km														
		CEC:		(Tech Info																				
300V RMS 	82842	NEC:	2	See	500	152.4	19.0	8.6	24.0Ω/M'	2.4Ω/M'	.273	6.93	120	76%	12	39.4	22	72.2						
		CMP		Chart 5	1000	304.8	42.0	19.1	78.7Ω/km	7.9Ω/km														
		CEC:		(Tech Info																				
300V RMS 	89841	NEC:	1	See	500	152.4	13.5	6.1	24.0Ω/M'	3.1Ω/M'	.202	5.13	120	76%	12	39.4	22	72.2						
		CMP		Chart 5	1000	304.8	27.0	12.3	78.7Ω/km	10.2Ω/km														
		CEC:		(Tech Info																				
300V RMS 	89842 <small>new</small>	NEC:	2	See	500	152.4	25.5	11.6	24.0Ω/M'	3.1Ω/M'	.305	7.75	120	76%	12	39.4	22	72.2						
		CMP		Chart 5	1000	304.8	49.0	22.2	78.7Ω/km	10.2Ω/km														
		CEC:		(Tech Info																				
300V RMS 	89842 <small>new</small>	NEC:	2	See	500	152.4	25.5	11.6	24.0Ω/M'	3.1Ω/M'	.305	7.75	120	76%	12	39.4	22	72.2						
		CMP		Chart 5	1000	304.8	49.0	22.2	78.7Ω/km	10.2Ω/km														
		CEC:		(Tech Info																				

DCR = DC Resistance • TC = Tinned Copper

*Capacitance between conductors.

**Capacitance between one conductor and other conductors connected to shield.

Industrial Data Solutions® — Industrial Data**EIA Industrial RS-485 PLTC/CM**

Description	Part No.	UL NEC/ C(UL) CEC Type	No. of Pairs	Color Code	Standard Lengths		Standard Unit Weight		Nom. DCR		Nominal OD		Nom. Imp. (Ω)	Nom. Vel. of Prop.	Nom. Capacitance				
					Ft.	m	Lbs.	kg	Cond.	Shield	Inch	mm			* pF/ Ft.	* pF/ m	** pF/ Ft.	** pF/ m	
22 AWG Stranded (7x30) TC Conductors • Twisted Pairs • Overall Beldfoil® Shield (100% Coverage) + TC Braid (90% Coverage) • Drain Wire[^]																			
Datalene® Insulation • Black UV Resistant PVC Jacket (CPE jacket optional)																			
	Oil Res II 300V	3105A[†]	NEC: CM PLTC CEC: CM FT1	1	See Chart (below)	500 1000 5000 [†]	152.4 304.8 1523.9	23.0 50.0 255.0	10.4 22.7 115.8	14.7Ω/M' 48.2Ω/km	2.8Ω/M' 9.2Ω/km	.284 7.21	120	78%	11.0	36.1	20.9	68.6	
																			For CPE jacketed version order Part No. YR44345
		3106A	NEC: CM PLTC CEC: CM FT1	1.5 [*]	White/Orange, Orange/White, Blue/White	500 1000 5000 [†]	152.4 304.8 1523.9	27.0 51.0 260.0	12.3 23.2 118.1	14.7Ω/M' 48.2Ω/km	2.8Ω/M' 9.2Ω/km	.300 7.62	120	78%	11.0	36.1	20.9	68.6	For CPE jacketed version order Part No. YR46721
		3107A[†]	NEC: CM PLTC CEC: CM FT1	2	See Chart (below)	1000 4000 5000 [†]	304.8 1219.2 1523.9	69.0 300.0 385.0	31.3 136.2 174.8	14.7Ω/M' 48.2Ω/km	1.8Ω/M' 5.9Ω/km	.356 9.04	120	78%	11.0	36.1	20.9	68.6	For CPE jacketed version order Part No. YR46792
		3108A	NEC: CM PLTC CEC: CM FT1	3	See Chart (below)	1000 2000	304.8 609.6	93.0 184.0	42.2 83.5	14.7Ω/M' 48.2Ω/km	1.5Ω/M' 4.9Ω/km	.420 10.67	120	78%	11.0	36.1	20.9	68.6	For CPE jacketed version order Part No. YR45287
	3109A	NEC: CM PLTC CEC: CM FT1	4	See Chart (below)	1000 2000	304.8 609.6	107.0 218.0	48.6 99.0	14.7Ω/M' 48.2Ω/km	1.4Ω/M' 4.6Ω/km	.420 10.67	120	78%	11.0	36.1	20.9	68.6	For CPE jacketed version order Part No. YR44768	

*3015A and 3107A are DMX512 Type.

[^]22 AWG stranded tinned copper drain wire.**AL Interlocked Armor • Datalene® Insulation • PVC Inner Jacket • Black UV Resistant PVC Outer Jacket**

300V	123107A <small>(NEW)</small>	NEC: CM PLTC CEC: CMG FT4	2	See Chart (below)	5000 ^{††}	1523.9	1140.0	514.1	14.7Ω/M' 48.2Ω/km	1.8Ω/M' 5.9Ω/km	.650 16.51	120	78%	11.0	36.1	20.9	68.6
------	--	------------------------------------	---	-------------------------	--------------------	--------	--------	-------	----------------------	--------------------	---------------	-----	-----	------	------	------	------

[^]22 AWG stranded tinned copper drain wire.

DCR = DC Resistance • TC = Tinned Copper

* Capacitance between conductors.

** Capacitance between one conductor and other conductors connected to shield.

[†] Final put-up length may vary -0 to +10% from length shown.^{††} Final put-up length may vary ±10% for spools or reels and ±5% for UnReel® cartons from length shown.^{*}All conductors are under the braid shield; one pair is under the Beldfoil shield.**Color Code Chart**

Pair No.	Color Combination
1	White/Blue Stripe Blue/White Stripe
2	White/Orange Stripe Orange/White Stripe
3	White/Green Stripe Green/White Stripe
4	White/Brown Stripe Brown/White Stripe