

Selection Guide

Shielded Multi-Pair Computer Cables
RS-232, RS-422, and RS-485 Applications*

Specifications		Cable Series**																	
		9804	8132	9829	8332	9501	8102	9729	8162	9990	9841	9680	9302*	8302	8777	9873	9773	8132FO	1419A
Conductor Size: (AWG)	28	✓	✓															✓	
	24			✓	✓	✓	✓	✓	✓	✓	✓								✓
	22											✓	✓	✓					
	20															✓			
	18																✓		
Page No.		5.26	5.27	5.30	5.29	5.11	5.31	5.35	5.44	5.37	5.28	5.15	5.17	5.32	5.40	5.42	5.42	5.14	5.15
Insulation:	S-R PVC				✓	✓							✓						
	Polyethylene			✓						✓	✓	✓				✓	✓		
	Polypropylene	✓												✓					
	Datalene®†		✓				✓	✓	✓									✓	✓
Shield:	Overall Foil					✓						✓	✓					✓	✓
	Individual Foil							✓	✓	✓				✓	✓	✓			
	Overall Foil/Braid	✓	✓	✓	✓		✓		✓		✓			✓					
	Braid Coverage	90%	65%	65%	65%		65%		65%		90%			65%					
Drain Wire: (see key below)		●	●	●	×	●	●	▲	▲	▲	●	●	●	×	▲	▲	▲	●	●
No. of Pairs Available:	1					✓					✓								
	2	✓	✓	✓	✓	✓	✓	✓	✓		✓		✓	✓				✓	✓
	3	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
	4	✓	✓	✓	✓	✓	✓	✓	✓		✓	✓	✓	✓				✓	✓
	5	✓	✓	✓	✓	✓	✓		✓				✓					✓	✓
	6			✓	✓	✓	✓	✓	✓	✓		✓	✓	✓	✓	✓	✓		✓
	7	✓		✓	✓	✓	✓		✓				✓						
	8		✓			✓	✓		✓					✓					✓
	9	✓		✓		✓		✓		✓		✓	✓		✓	✓	✓		
	10			✓	✓	✓	✓		✓					✓					
	11								✓						✓	✓			
	12	✓		✓					✓		✓				✓	✓	✓		
	12.5		✓		✓		✓					✓		✓				✓	✓
	13	✓																	
	15				✓	✓	✓	✓	✓				✓	✓	✓	✓	✓		✓
	17								✓						✓				
	18	✓	✓	✓	✓		✓		✓					✓					✓
	19					✓			✓				✓		✓				
	25	✓	✓	✓	✓	✓	✓		✓	✓				✓					✓
	27								✓				✓		✓				
31	✓																		
37														✓					
50					✓														
Capacitance †† (pF/ft.)		15.5	11.0	15.5	30.0	30.0	12.5	12.5	12.5	25.0	12.8	15.5	35.0	35.0	30.0	30.0	30.0	11.0	13.0

S-R = Semi-rigid

* Refer to specifications for recommendations.

** All cables are UL-listed.

† Foam high density polyethylene.

†† Capacitance may vary on some cables.

◆ Standard PVC Insulation, solid conductors.

Drain Wire Key:

- = Drain wire overall.
- ▲ = Drain wire each pair.
- × = No drain wire.