


# Unshielded

Telephone Cables


Audio, Control and Instrumentation Cables

Description	Part No.	UL NEC/ C(UL) CEC Type	No. of Pairs	Color Code	Standard Lengths		Standard Unit Weight		Insulation Thickness		Jacket Thickness		Nominal OD	
					Ft.	m	Lbs.	kg	Inch	mm	Inch	mm	Inch	mm

**24 AWG Solid Tinned Copper Conductors • Twisted Pairs**

<b>PVC Insulation • Chrome PVC Jacket</b>															
	UL AWM Style 2576 (150V 80°C)	<b>9562</b>	NEC:	2	See Chart 4 (Tech Info Section)	U-500	U-152.4	10.5	4.8	.010	.25	.032	.81	.199	5.05
			CMG			500	152.4	9.0	4.1						
			CEC:			U-1000	U-304.8	20.0	9.1						
			CMG FT4			1000	304.8	18.0	8.2						
	<b>9566</b>	NEC:	6	See Chart 4 (Tech Info Section)	U-500	U-152.4	21.5	9.8	.010	.25	.032	.81	.289	7.34	
		CMG			500	152.4	23.5	10.7							
		CEC:			U-1000	U-304.8	42.0	19.1							
		CMG FT4			1000	304.8	45.0	20.5							
	<b>9570</b>	NEC:	10	See Chart 4 (Tech Info Section)	500	152.4	31.5	14.3	.010	.25	.035	.89	.310	7.87	
		CMG			1000	304.8	63.0	28.6							
		CEC:													
		CMG FT4													
<b>9585</b>	NEC:	25	See Chart 4 (Tech Info Section)	500	152.4	74.0	33.6	.010	.25	.040	1.02	.480	12.19		
	CMG			1000	304.8	144.0	65.5								
	CEC:														
	CMG FT4														

**22 AWG Solid Tinned Copper Conductors • Twisted Pairs**

<b>PVC Insulation • Chrome PVC Jacket</b>																
	UL AWM Style 2576 (150V 80°C)	<b>8740</b>	NEC:	1	See Chart 3 (Tech Info Section)	U-500	U-152.4	7.5	3.4	.010	.25	.032	.81	.156	3.96	
			CMG			U-1000	U-304.8	14.0	6.4							
			CEC:													
			CMG FT4													
		<b>8741</b>	NEC:	2	See Chart 3 (Tech Info Section)	U-500	U-152.4	13.5	6.1	.010	.25	.032	.81	.230	5.84	
			MPG, CMG			U-1000	U-304.8	25.0	11.3							
			CEC:			1000	304.8	27.0	12.2							For stranded conductor Plenum versions of 8741, see 88741 or 82741.
			CMG FT4													
		<b>8742</b>	NEC:	3	See Chart 3 (Tech Info Section)	500	152.4	17.0	7.7	.010	.25	.032	.81	.242	6.15	
			MPG, CMG			U-1000	U-304.8	31.0	14.1							
			CEC:			1000	304.8	33.0	15.0							For stranded conductor Plenum version of 8742, see 82742.
			CMG FT4													
<b>8757</b>	NEC:	4	See Chart 3 (Tech Info Section)	500	152.4	20.0	9.1	.010	.25	.032	.81	.264	6.71			
	MPG, CMG			U-1000	U-304.8	38.0	17.2									
	CEC:			1000	304.8	40.0	18.2							For stranded conductor Plenum versions of 8757, see 88757 or 82757.		
	CMG FT4															
<b>8743</b>	NEC:	6	See Chart 3 (Tech Info Section)	U-500	U-152.4	26.5	12.0	.010	.25	.032	.81	.293	7.44			
	MPG, CMG			U-1000	U-304.8	51.0	23.1									
	CEC:			1000	304.8	53.0	24.1							For stranded conductor Plenum version of 8743, see 82743.		
	CMG FT4															
<b>9160</b>	NEC:	8	See Chart 3 (Tech Info Section)	500	152.4	35.5	16.1	.010	.25	.035	.89	.323	8.20			
	MPG, CMG			1000	304.8	71.0	32.3									
	CEC:															
	CMG FT4															
<b>8744</b>	NEC:	9	See Chart 3 (Tech Info Section)	1000	304.8	79.0	35.9	.010	.25	.035	.89	.350	8.89			
	MPG, CMG															
	CEC:															
	CMG FT4															



For more information, contact Belden Technical Support: 1-800-BELDEN-1 • www.belden.com

Belden114@cablecon.kr / 0707-434-7704 / Fax. 02-744-0909 / www.CableCon.co.kr