



# Unshielded


## Audio, Control and Instrumentation Cables

Description	Part No.	UL NEC/ C(UL) CEC Type	No. of Pairs	Color Code	Standard Lengths		Standard Unit Weight		Insulation Thickness		Jacket Thickness		Nominal OD	
					Ft.	m	Lbs.	kg	Inch	mm	Inch	mm	Inch	mm


### 20 AWG Stranded (7x28) Tinned Copper Conductors • Twisted Pairs

PVC Insulation • Chrome PVC Jacket																
	8205	NEC:	1	See Chart 3 (Tech Info Section)	100	30.5	2.6	1.2	.013	.33	.025	.64	.180	4.57		
		CMG:			U-500	U-152.4	9.0	4.1								
		CEC:			500	152.4	9.0	4.1								
		CMG FT4			U-1000	U-304.8	18.0	8.2								
					1000	304.8	18.0	8.2								
	9750	NEC:	3	See Chart 3 (Tech Info Section)	500	152.4	26.5	12.0	.013	.33	.035	.89	.299	7.59		
		CMG:			1000	304.8	50.0	22.7								
		CEC:														
		CMG FT4														
	9751	NEC:	6	See Chart 3 (Tech Info Section)	100	30.5	9.1	4.1	.013	.33	.035	.89	.366	9.30		
		CMG:			500	152.4	45.0	20.5								
		CEC:			1000	304.8	89.0	40.5								
		CMG FT4														
	9752	NEC:	9	See Chart 3 (Tech Info Section)	100	30.5	13.1	5.9	.013	.33	.035	.89	.429	10.90		
		CMG:			500	152.4	65.5	29.8								
		CEC:			1000	304.8	125.0	56.8								
		CMG FT4														
9755	NEC:	15	See Chart 3 (Tech Info Section)	100	30.5	17.9	8.1	.013	.33	.040	1.02	.545	13.84			
	CMG:			1000	304.8	194.0	88.2									
	CEC:															
	CMG FT4															

### 19 AWG Solid Bare Copper Conductors • Twisted Pair

PVC Insulation • Chrome PVC Jacket															
	8486	NEC:	1	Brown, Tan	U-500	U-152.4	9.5	4.3	.015	.38	.025	.64	.182	4.62	
		CM			U-1000	U-304.8	18.0	8.2							
		CEC:			1000	304.8	19.0	8.6							
		CM													

### 18 AWG Stranded (7x26) Tinned Copper Conductors • Twisted Pair

PVC Insulation • Chrome PVC Jacket															
	8461	NEC:	1	Black, White	100	30.5	3.2	1.4	.022	.56	.028	.71	.234	5.94	
		CMG:			U-500	U-152.4	14.0	6.4							
		CEC:			500	152.4	13.5	6.1							
		CMG FT4			U-1000	U-304.8	26.0	11.8							
					1000	304.8	27.0	12.2							