

DBS Cable

Series 6

Description	Part No.	UL NEC/ C(UL) CEC Type	Standard Lengths		Standard Unit Weight		Conductor (stranding) Diameter Nom. DCR	Nominal Core OD		Shielding Materials Nom. DCR	Nominal OD		Nom. Imp. (Ω)	Nom. Vel. of Prop.	Nominal Capacitance		Nominal Attenuation		
			Ft.	m	Lbs.	kg		Inch	mm		Inch	mm			pF/Ft.	pF/m	MHz	dB/100 Ft.	dB/100m

Series 6 • 18 AWG Solid .040" Bare Copper or Bare Copper-covered Steel Conductor (see below) • Duobond® II + AL Braid Shield (60% Coverage) (cont'd)

Gas-injected Foam Polyethylene Insulation • Black PVC Jacket

80°C	1839A	—	1000	304.8	40.0	18.1	18 AWG (solid) .040"	.180	4.57	Duobond II* + 60% Aluminum Braid	.270 x .405	6.86 x 10.29	75	83%	16.2	53.1	5 55 211 500 750 862 1000 1450 1800 2250	.5 1.4 2.6 4.1 5.1 5.5 6.0 7.8 8.6 9.8	1.6 4.6 8.5 13.5 16.7 18.0 19.7 25.6 28.2 32.2
------	--------------	---	------	-------	------	------	-------------------------	------	------	-------------------------------------------	-------------------	--------------------	----	-----	------	------	---------------------------------------------------------------------	-------------------------------------------------------------------	---------------------------------------------------------------------------

.045" (1.14mm) copper-covered steel, static ground.

80°C	1840A	—	500 1000	152.4 304.8	37.5 74.0	17.0 33.6	18 AWG (solid) .040"	.180	4.57	Duobond II* + 60% Aluminum Braid	.273 x .703	6.93 x 17.86	75	83%	16.2	53.1	5 55 211 500 750 862 1000 1450 1800 2250	.5 1.4 2.6 4.1 5.1 5.5 6.0 7.8 8.6 9.8	1.6 4.6 8.5 13.5 16.7 18.0 19.7 25.6 28.2 32.2
------	--------------	---	-------------	----------------	--------------	--------------	-------------------------	------	------	-------------------------------------------	-------------------	--------------------	----	-----	------	------	---------------------------------------------------------------------	-------------------------------------------------------------------	---------------------------------------------------------------------------

.045" (1.14mm) copper-covered steel static ground.

80°C	1841A	NEC: CATV CM CEC: CM	1000	304.8	66.0	30.0	18 AWG (solid) .040"	.180	4.57	Duobond II* + 60% Aluminum Braid	.273 x .595	6.93 x 15.11	75	83%	16.2	53.1	5 55 211 500 750 862 1000 1450 1800 2250	.5 1.4 2.6 4.1 5.1 5.5 6.0 7.8 8.6 9.8	1.6 4.6 8.5 13.5 16.7 18.0 19.7 25.6 28.2 32.2
------	--------------	-------------------------------	------	-------	------	------	-------------------------	------	------	-------------------------------------------	-------------------	--------------------	----	-----	------	------	---------------------------------------------------------------------	-------------------------------------------------------------------	---------------------------------------------------------------------------

Gas-injected Foam Polyethylene Insulation • PVC Jacket (Black, Gray or White)

80°C	1839AC	—	1000 [▲]	304.8	44.0	20.0	18 AWG (solid) .040"	.180	4.57	Duobond II* + 60% Aluminum Braid	.270 x .405	6.86 x 10.29	75	83%	16.2	53.1	5 55 211 500 750 862 1000 1450 1800 2250 3000	.5 1.4 2.6 4.1 5.1 5.5 6.0 7.8 8.6 9.8 11.3	1.6 4.6 8.5 13.5 16.7 18.0 19.7 25.6 28.2 32.2 37.1
------	---------------	---	-------------------	-------	------	------	-------------------------	------	------	-------------------------------------------	-------------------	--------------------	----	-----	------	------	-----------------------------------------------------------------------------	---------------------------------------------------------------------------	-----------------------------------------------------------------------------------

[▲]1000 ft. put-up not available in White.
.045" (1.14mm) copper-covered steel static ground.

80°C	1840AC	—	500	152.4	38.0	17.2	18 AWG (solid) .040"	.180	4.57	Duobond II* + 60% Aluminum Braid	.273 x .703	6.93 x 17.86	75	83%	16.2	53.1	5 55 211 500 750 862 1000 1450 1800 2250 3000	.5 1.4 2.6 4.1 5.1 5.5 6.0 7.8 8.6 9.8 11.3	1.6 4.6 8.5 13.5 16.7 18.0 19.7 25.6 28.2 32.2 37.1
------	---------------	---	-----	-------	------	------	-------------------------	------	------	-------------------------------------------	-------------------	--------------------	----	-----	------	------	-----------------------------------------------------------------------------	---------------------------------------------------------------------------	-----------------------------------------------------------------------------------

.045" (1.14mm) copper-covered steel static ground.

80°C	1841AC	NEC: CATV CM CEC: CM	500	152.4	32.5	14.7	18 AWG (solid) .040"	.180	4.57	Duobond II* + 60% Aluminum Braid	.273 x .595	6.93 x 15.11	75	83%	16.2	53.1	5 55 211 500 750 862 1000 1450 1800 2250 3000	.5 1.4 2.6 4.1 5.1 5.5 6.0 7.8 8.6 9.8 11.3	1.6 4.6 8.5 13.5 16.7 18.0 19.7 25.6 28.2 32.2 37.1
------	---------------	-------------------------------	-----	-------	------	------	-------------------------	------	------	-------------------------------------------	-------------------	--------------------	----	-----	------	------	-----------------------------------------------------------------------------	---------------------------------------------------------------------------	-----------------------------------------------------------------------------------

AL = Aluminum • BC = Bare Copper • BCAC = Bare Copper Anti-corrosion • BCCS = Bare Copper-covered Steel • DCR = DC Resistance

*Duobond II = Bonded Duofoil® (100% coverage) + aluminum braid (67% coverage).