

Computer and Instrumentation Cable

75 Ohm and 93 Ohm Coax

Description	Part No.	UL NEC/ C(UL) CEC Type	Standard Lengths		Standard Unit Weight		Conductor (stranding) Diameter Nom. DCR	Nominal Core OD		Shielding Materials Nom. DCR	Nominal OD		Nom. Imp. (Ω)	Nom. Vel. of Prop.	Nominal Capacitance		Nominal Attenuation		
			Ft.	m	Lbs.	kg		Inch	mm		Inch	mm			pF/Ft.	pF/m	MHz	dB/ 100 Ft.	dB/ 100m

75 Ohm • RG-11/U Type • 14 AWG Solid Bare Copper-covered Steel Conductor • Duobond IV Quad Shield (100% Coverage)

Plenum • Foam FEP Insulation • Gray Fluorocopolymer Jacket

150°C	3095A	NEC: CMP; PLTC CEC: CMP FT6	1000	304.8	76.0	34.5	14 AWG (solid) .064" BCCS 11.0Ω/M' 36.1Ω/km	.280	7.11	Duobond IV* Quad Shield 3.9Ω/M' 12.8Ω/km	.387	9.83	75	82%	16.5	54.1	1	.20	.70	.39	1.30	1.20	3.90	1.70	5.60	2.50	8.20	3.50	11.50
-------	--------------	---	------	-------	------	------	--	------	------	---	------	------	----	-----	------	------	---	-----	-----	-----	------	------	------	------	------	------	------	------	-------

Suitable for Outdoor and Direct Burial applications.
Tap marks every 2.6 meters to aid users in installation.

93 Ohm • RG-62B/U Type • 24 AWG Stranded (7x32) .024" Bare Copper-covered Steel Conductor • BC Braid Shield (95% Coverage)

Semi-solid Polyethylene Insulation • Black Non-contaminating PVC Jacket

UL AWM Style 1354 (30V 60°C) VW-1	8255	NEC: CMX CEC: CMX	500	152.4	16.5	7.5	24 AWG (7x32) .024" 59.0Ω/M' 193.6Ω/km	.146	3.71	BC Braid 95% Shield Coverage BCCS 2.9Ω/M' 9.5Ω/km	.242	6.15	93	84%	13.5	44.3	1	.3	1.0	.9	3.0	2.0	6.6	2.9	9.5	4.2	13.8	6.1	20.0	8.6	28.2	10.1	33.1	11.1	36.4
--	-------------	----------------------------	-----	-------	------	-----	--	------	------	--	------	------	----	-----	------	------	---	----	-----	----	-----	-----	-----	-----	-----	-----	------	-----	------	-----	------	------	------	------	------

MIL-C-17D

93 Ohm • RG-62/U Type • JAN-C-17A • 22 AWG Solid .025" Bare Copper-covered Steel Conductor • BC Braid Shield (95% Coverage)

Semi-solid Polyethylene Insulation • Black PVC Jacket

75°C	8254	—	U-500	U-152.4	18.0	8.2	22 AWG (solid) .025" 41.2Ω/M' 135.1Ω/km	.146	3.71	BC Braid 95% Shield Coverage BCCS 2.9Ω/M' 9.5Ω/km	.238	6.05	93	84%	13.5	44.3	1	.3	.8	.9	2.8	1.9	6.2	2.7	8.9	3.8	12.5	5.3	17.4	7.3	23.9	8.2	26.9	8.7	28.5
------	-------------	---	-------	---------	------	-----	---	------	------	--	------	------	----	-----	------	------	---	----	----	----	-----	-----	-----	-----	-----	-----	------	-----	------	-----	------	-----	------	-----	------

93 Ohm • RG-62A/U Type • 22 AWG Solid .025" Bare Copper-covered Steel Conductor • Bare Copper Braid Shield (95% Coverage)

Semi-solid Polyethylene Insulation • Black High-density Polyethylene Jacket

Flooded Burial 80°C	9228	—	500	152.4	15.0	6.8	22 AWG (solid) .025" 41.2Ω/M' 135.1Ω/km	.146	3.71	BC Braid 95% Shield Coverage BCCS 2.9Ω/M' 9.5Ω/km	.242	6.15	93	84%	13.5	44.3	1	.3	.8	.9	2.8	1.9	6.2	2.7	8.9	3.8	12.5	5.3	17.4	7.3	23.9	8.2	26.9	8.7	28.5
------------------------	-------------	---	-----	-------	------	-----	---	------	------	--	------	------	----	-----	------	------	---	----	----	----	-----	-----	-----	-----	-----	-----	------	-----	------	-----	------	-----	------	-----	------

Suitable for Outdoor and Direct Burial applications.

Semi-solid Polyethylene Insulation • Black PVC Jacket

UL AWM Style 1478 (30V 60°C)	9268	NEC: CM CL2 CEC: CM	500	152.4	20.0	9.1	22 AWG (solid) .025" 41.2Ω/M' 135.1Ω/km	.146	3.71	BC Braid 95% Shield Coverage BCCS 2.9Ω/M' 9.5Ω/km	.260	6.60	93	84%	13.5	44.3	1	.3	.8	.9	2.8	1.9	6.2	2.7	8.9	3.8	12.5	5.3	17.4	7.3	23.9	8.2	26.9	8.7	28.5
------------------------------------	-------------	------------------------------	-----	-------	------	-----	---	------	------	--	------	------	----	-----	------	------	---	----	----	----	-----	-----	-----	-----	-----	-----	------	-----	------	-----	------	-----	------	-----	------

IBM P/N 5252750 • Includes Mylar® tape as a moisture barrier for improved outdoor reliability.

UL AWM Style 1478 (30V 60°C)	9269	NEC: CM CL2 CEC: CM	U-500	U-152.4	18.5	8.4	22 AWG (solid) .025" 41.2Ω/M' 135.1Ω/km	.146	3.71	BC Braid 95% Shield Coverage BCCS 2.9Ω/M' 9.5Ω/km	.239	6.07	93	84%	13.5	44.3	1	.3	.8	.9	2.8	1.9	6.2	2.7	8.9	3.8	12.5	5.3	17.4	7.3	23.9	8.2	26.9	8.7	28.5
------------------------------------	-------------	------------------------------	-------	---------	------	-----	---	------	------	--	------	------	----	-----	------	------	---	----	----	----	-----	-----	-----	-----	-----	-----	------	-----	------	-----	------	-----	------	-----	------

IBM P/N 323921 P-MSHA SC-1823**

*U-1000 put-up also available in Orange, Beige or Chrome.

BC = Bare Copper • BCCS = Bare Copper-covered Steel • DCR = DC Resistance • FEP = Fluorinated Ethylene Propylene

Mylar is a DuPont trademark.

Contact the Belden Customer Service Department for a Comprehensive Connector Cross Reference. **1-800-BELDEN-1**.

For cables manufactured to latest government revision or other MIL-SPEC requirements, please contact your nearest Belden regional Sales Office.

* Duobond IV = Bonded Duofoil® (100% coverage) + aluminum braid (67% coverage) + Duofoil (100% coverage) + aluminum braid (46% coverage).

** Pennsylvania Department of Environmental Resources and United States Mine Safety and Health Administration Certification.