


**Multi-Conductor**

## Power and Control Cables

Description	Part No.	No. of Cond.	Standard Lengths		Standard Unit Weight		Jacket Color	Conductor AWG (stranding)	Nom. Insulation Thickness		Nom. Jacket Thickness		Nominal OD	
			Ft.	m	Lbs.	kg			Inch	mm	Inch	mm	Inch	mm

**SO Oil-Resistant Rubber Jacket** • Smooth Jacket • UL/CSA Listed**600V, 60°C** • Conductors Cabled with Fillers • Paper Tape Separator • Color Code: See Chart 2 (Tech Info Section)

	<b>9420</b>	5	100	30.5	13.3	6.0	Black	16 (65x34) BC	.033	.84	.084	2.13	.506	12.85
			500	152.4	73.5	33.4								
			1000	304.8	143.0	65.0								
	<b>9422</b>	7	100	30.5	18.5	8.4	Black	16 (65x34) BC	.033	.84	.083	2.11	.581	14.76
			500	152.4	101.0	45.9								
			1000	304.8	201.0	91.4								
	<b>9424</b>	9	100	30.5	29.6	13.4	Black	16 (65x34) BC	.033	.84	.100	2.54	.720*	18.29
			500	152.4	150.5	68.4								
			1000	304.8	288.0	130.9								
<b>9425</b>	12	100	30.5	32.6	14.8	Black	16 (65x34) BC	.033	.84	.100	2.54	.720	18.29	
		500	152.4	165.5	75.2									
		1000	304.8	318.0	144.5									
<b>9427</b>	16	100	30.5	39.5	17.9	Black	16 (65x34) BC	.033	.84	.100	2.54	.787	19.99	
		500	152.4	197.5	89.8									
		1000	304.8	395.0	179.6									
<b>9429</b>	20	100	30.5	48.4	22.0	Black	16 (65x34) BC	.033	.84	.100	2.54	.862	21.89	
		500	152.4	233.0	105.9									
		1000	304.8	466.0	211.8									

BC = Bare Copper • CPE = Chlorinated Polyethylene

\*Fillers added in the center.