





2-Conductor

UL/CSA Types: SPT-1, SPT-2, SP-1 and HPN

Description	Part No.	Standard Lengths		Standard Unit Weight		Jacket Color	Conductor AWG (stranding)	Nom. Insulation Thickness		Nom. Jacket Thickness		Nominal OD	
		Ft.	m	Lbs.	kg			Inch	mm	Inch	mm	Inch	mm
SPT-1 PVC Parallel Lamp Cord • UL/CSA Listed													
300V, 60°C • One Conductor Polarity Ribbed													
	19122	250 [†]	76.2	5.8	2.6	Brown, White, Black, Silver-Gray	18 (42x34) BC	.032	.81	—	—	.110	2.79
		1000 ^{††}	304.8	21.0	9.5							x	x
	8888*	250	76.2	5.5	2.5	Brown	18 (42x34) BC	.032	.81	—	—	.110	2.79
		U-1000	U-304.8	21.0	9.5							Brown, Gray	x
												.207	5.26
SPT-2 PVC Parallel Lamp Cord • UL/CSA Listed													
300V, 60°C • One Conductor Polarity Ribbed													
	19123	250 [†]	76.2	7.8	3.5	Brown, White, Black	18 (42x34) BC	.049	1.24	—	—	.144	3.66
												x	x
	19126	250 [†]	76.2	9.8	4.4	Brown, Black	16 (65x34) BC	.048	1.22	—	—	.155	3.94
												x	x
												.299	7.59
SP-1 Rubber Parallel Lamp Cord • UL Listed													
300V, 60°C • One Conductor Polarity Ribbed													
	19115*	250 [†]	76.2	6.8	3.1	Brown, Black	18 (41x34) BC	.035	.89	—	—	.123	3.12
												x	x
												.227	5.77
HPN CPE Heater Cord • UL/CSA Listed													
300V, 90°C													
	19405	250 [†]	76.2	7.8	3.5	Black	18 (41x34) BC	.047	1.18	—	—	.140	3.56
		1000 [†]	304.8	31.0	14.1							x	x
	19404	250 [†]	76.2	9.8	4.4	Black	16 (105x36) BC	.047	1.18	—	—	.152	3.86
		1000 [†]	304.8	39.0	17.7							x	x
												.300	7.62

BC = Bare Copper • CPE = Chlorinated Polyethylene

*Not CSA recognized.

[†]Put-ups may contain more than one piece. Minimum length of any one piece is 50 ft.^{††}Put-ups may contain more than one piece. Minimum length of any one piece is 100 ft.

2-Conductor

UL/CSA Types: SJ, SJO, SJTOW, SO

Description	Part No.	Standard Lengths		Standard Unit Weight		Jacket Color	Conductor AWG (stranding)	Nom. Insulation Thickness		Nom. Jacket Thickness		Nominal OD	
		Ft.	m	Lbs.	kg			Inch	mm	Inch	mm	Inch	mm

SJ Rubber Jacket • Smooth Jacket • UL/CSA Listed**300V, 60°C** • Paper Tape Separator • Color Code: Black, White

8478	250	76.2	10.8	4.9	Black	18 (42x34) BC	.032	.81	.035	.89	.290	7.37
	1000	304.8	48.0	21.8								
8472	250	76.2	12.8	5.8	Black	16 (65x34) BC	.033	.84	.035	.89	.315	8.00

SJO Oil-Resistant Rubber Jacket • Smooth Jacket • UL/CSA Listed**300V, 90°C** • Paper Tape Separator • Color Code: Black, White

19227	250 [†]	76.2	11.0	5.0	Black	18 (16x30) BC	.031	.79	.035	.89	.290	7.37
	19228	250 [†]	76.2	13.5								
					Black	16 (26x30) BC	.031	.79	.035	.89	.315	8.00

SJTOW Belflex® Matte Black Premium PVC • Smooth Jacket • UL/CSA Listed**300V, 105°C** • Paper Tape Separator • International Color Code: Light Blue, Brown

VW-1	19506*	250	76.2	11.0	5.0	Matte Black	18 (42x34) BC	.032	.81	.035	.89	.290	7.34
	19507*	250	76.2	13.5	6.1	Matte Black	16 (65x34) BC	.033	.84	.037	.94	.319	8.10
	19508*	250	76.2	17.0	7.7	Matte Black	14 (41x30) BC	.033	.84	.032	.81	.348	8.84

SO Oil-Resistant Rubber Jacket • Smooth Jacket • UL/CSA Listed**600V, 90°C** • Cotton Serve Separator • Color Code: Black, White

	19204	250 [†]	76.2	18.5	8.4	Black	18 (42x34) BC	.032	.81	.065	1.65	.360	9.14
	19203	250 [†]	76.2	19.0	8.6	Black	16 (65x34) BC	.033	.84	.065	1.65	.385	9.78
	19202	250 [†]	76.2	37.3	16.9	Black	14 (41x30) BC	.048	1.22	.085	2.16	.523	13.28

600V, 90°C • Paper Tape Separator • Color Code: Black, White

	19201	250 [†]	76.2	52.8	24.0	Black	12 (65x30) BC	.051	1.30	.100	2.54	.610	15.49
--	--------------	------------------	------	------	------	-------	---------------------	------	------	------	------	------	-------

BC = Bare Copper

*These constructions are approved as water-resistant, oil-resistant and for outdoor use.


[†]Put-ups may contain more than one piece. Minimum length of any one piece is 50 ft.

2-Conductor


UL/CSA Types: STOW, SV, SVT

Description	Part No.	Standard Lengths		Standard Unit Weight		Jacket Color	Conductor AWG (stranding)	Nom. Insulation Thickness		Nom. Jacket Thickness		Nominal OD	
		Ft.	m	Lbs.	kg			Inch	mm	Inch	mm	Inch	mm


STOW Belflex® Matte Black Premium PVC • Smooth Jacket • UL/CSA Listed**600V, 105°C • Paper Tape Separator • International Color Code: Light Blue, Brown**

	19500*	250	76.2	16.0	7.3	Matte Black	18 (42x34) BC	.032	.81	.070	1.78	.360	9.14
	19501*	250	76.2	18.8	8.5	Matte Black	16 (65x34) BC	.033	.84	.070	1.78	.386	9.80
	19502*	250	76.2	34.0	15.5	Matte Black	14 (41x30) BC	.049	1.24	.089	2.26	.524	13.31


SV Rubber Jacket • Serrated Jacket • UL/CSA Listed**300V, 60°C • Cotton Serve Separator • Color Code: Black, White**

	8452	250	76.2	9.5	4.3	Black	18 (42x34) BC	.017	.43	.037	.94	.245	6.22
		U-500	U-152.4	18.5	8.4								
		500	152.4	17.0	7.7								
		U-1000	U-304.8	36.0	16.3								
		1000	304.8	38.0	17.3								

SV Rubber Jacket • Smooth Jacket • UL/CSA Listed**300V, 60°C • Cotton Serve Separator • Color Code: Black, White**

	19120	250 [†]	76.2	8.8	4.0	Black	18 (42x34) BC	.017	.43	.037	.94	.245	6.22

SVT PVC Jacket • Serrated Jacket • UL/CSA Listed**300V, 60°C • Paper Tape Separator • Color Code: Black, White**

	19140	250 [†]	76.2	8.8	4.0	Black, Gray	18 (42x34) BC	.018	.46	.036	.91	.243	6.17

BC = Bare Copper

*These constructions are approved as water-resistant, oil-resistant and for outdoor use.

†Put-ups may contain more than one piece. Minimum length of any one piece is 50 ft.