


## 2-Conductor


UL/CSA Types: STOW, SV, SVT

Description	Part No.	Standard Lengths		Standard Unit Weight		Jacket Color	Conductor AWG (stranding)	Nom. Insulation Thickness		Nom. Jacket Thickness		Nominal OD	
		Ft.	m	Lbs.	kg			Inch	mm	Inch	mm	Inch	mm


**STOW Belflex® Matte Black Premium PVC • Smooth Jacket • UL/CSA Listed**

<b>600V, 105°C • Paper Tape Separator • International Color Code: Light Blue, Brown</b>													
	<b>19500*</b>	250	76.2	16.0	7.3	Matte Black	18 (42x34) BC	.032	.81	.070	1.78	.360	9.14
	<b>19501*</b>	250	76.2	18.8	8.5	Matte Black	16 (65x34) BC	.033	.84	.070	1.78	.386	9.80
	<b>19502*</b>	250	76.2	34.0	15.5	Matte Black	14 (41x30) BC	.049	1.24	.089	2.26	.524	13.31


**SV Rubber Jacket • Serrated Jacket • UL/CSA Listed**

<b>300V, 60°C • Cotton Serve Separator • Color Code: Black, White</b>													
	<b>8452</b>	250	76.2	9.5	4.3	Black	18 (42x34) BC	.017	.43	.037	.94	.245	6.22
		U-500	U-152.4	18.5	8.4								
		500	152.4	17.0	7.7								
		U-1000	U-304.8	36.0	16.3								
		1000	304.8	38.0	17.3								

**SV Rubber Jacket • Smooth Jacket • UL/CSA Listed**

<b>300V, 60°C • Cotton Serve Separator • Color Code: Black, White</b>													
	<b>19120</b>	250 <sup>†</sup>	76.2	8.8	4.0	Black	18 (42x34) BC	.017	.43	.037	.94	.245	6.22

**SVT PVC Jacket • Serrated Jacket • UL/CSA Listed**

<b>300V, 60°C • Paper Tape Separator • Color Code: Black, White</b>													
	<b>19140</b>	250 <sup>†</sup>	76.2	8.8	4.0	Black, Gray	18 (42x34) BC	.018	.46	.036	.91	.243	6.17

BC = Bare Copper

\*These constructions are approved as water-resistant, oil-resistant and for outdoor use.

<sup>†</sup>Put-ups may contain more than one piece. Minimum length of any one piece is 50 ft.